

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A018150
VIN: 085020

SALES | RENTALS | PARTS | SERVICE

| | |
|-------------------------------------|---------------------------------------|
| Allentown, PA: 800-383-8894 | Jacksonville, FL: 800-828-3055 |
| Baltimore, MD: 888-601-7500 | Little Rock, AR: 833-424-8944 |
| Boston, MA: 800-854-5310 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Richmond, VA: 866-839-3495 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

| components | description |
|----------------------|--|
| CAPACITY | Heavy Duty Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed) |
| OVERALL LENGTH | 48' - 80'Extendable Trailer |
| OVERALL WIDTH | 8' 6" |
| KING PIN SETTING | 24" |
| UPPER COUPLER PLATE | 1/4" |
| | * * 3rd Gladhand Design to Operate Lock and Release on Locking Pins * * |
| | * * Sign stating Locking Pin Release above 3rd Gladhand * * |
| | * * Eliminate Box, Valving, and Bracket on Side of Trailer * * |
| | * * Tapered Front Plate to allow Easier Hook Up for Multiple Trucks * * |
| UPPER COUPLER HEIGHT | 48" |
| BULKHEAD | Removable Steel - 48" - No Side Return |
| | * * Last Post on Headboards to Cap Off Headboards * * |
| MAINFRAME | 26" Fabricated - PreCambered I-Beams |
| | * * * 11' Front Deck and 37' Rear Deck * * * |
| | *****Insert 3/16" - Approx 33" Wide - Plate Under Top Flange From Flange to Flange to Allow Customer to walk from Deck to Deck When Trailer is Extended***** |
| SIDE RAILS | 6" - 6.5# Per Foot |
| | * * New Tapered Corner Design * * |
| | * * Pipe and Bullet Connection at Connection Points to help maintain squareness* |
| FLOOR SILLS | 4" I-Beam 12" O.C. STD Pkg Capacity |
| FLOOR DECKING | 1-1/8" Apitong |
| WINCH TRACK | Steel Slide Entire Length of Drivers Side |
| WINCHES | 12 |
| STRAPS | None |
| LANDING GEAR | Two Speed |
| | * * Landing Gear Bracing to one Horizontal Brace from Box to Box * * |
| SUSPENSIONS | Spring Ride - Fixed - Hutchens - 3 Axles (-388#) |
| DUMP VALVE | None |
| SCALES | None |
| AXLES | (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Spring Ride |
| | ***** 5/8 Wall Axles***** |
| AXLE SPACING | 49" |
| PARKING BRAKES | 3 Axle |
| DUST SHEILDS | None |
| WHEELS | 11R22.5 |
| ANTI-SAIL MUD FLAPS | On Rear Skirt |
| STAKE POCKETS | 4" Deep - 24" O.C. & 6 Across Front, 3 Across Rear |
| RUB BAND STEEL | 1/4" X 2-1/2" |
| PIPE SPOOLS | Double |
| DOCK BUMPERS | Rubber Inboard |

| | |
|---------------|---|
| TIRE CARRIERS | None |
| TOOLBOXES | None |
| TOOLBOX TYPE | None |
| LIGHTS | Sealed Wiring Harness w/ LED Pkg |
| | ** Wiring to be Rerouted Per Pictures of Competition (Eliminate Welded Brackets to Main Frame Bottom Flange. ** |
| PAINT | Black |
| CUSTOM 1 | None |
| CUSTOM 2 | None |

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.