




Resale Inventory  
 A018745  
 VIN: 173379

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, "DARKWING" ALUMINUM DROP PLATFORM 
<b>DIMENSIONS</b>	
LENGTH	53'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 36" at the bumper.
DROP HEIGHT	25", located at 10'-6" from front.
<b>COUPLING</b>	
COUPLER PLATE	1/4", galvanised (G164) 80 000 psi steel, plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	48".
<b>STRUCTURE</b>	42" center to center Frame with "CAMBER".
<b>FLANGES</b>	3/8" x 5" , 100 000 psi steel in gooseneck and the remaining. Top, "T" shaped aluminum extrusion (6061-T6), with 2 Cargo Rail integrated by flange. Bottom, aluminum extrusion (6061-T6) 4" x 1 1/2".
<b>WEB</b>	3/16" plate in king pin area, 80 000 psi steel and the remaining. 1/4" plate, polished aluminum (5454-H34), riveted at 3" c/c, 24 3/4" high including flanges.
<b>GOOSENECK</b>	11 1/4" high, 48" straight behind king pin, galvanized steel (G164).
<b>CROSSMEMBERS</b>	4" high extruded aluminum I beams, 16" c/c in gooseneck and the remaining 12" c/c. One additional crossmember at rear bumper.
<b>FLOOR</b>	Structural aluminum extrusions, flat type, inverted "T", 1 1/4" high with 3 Apitong or equivalent planks.
<b>FLOOR FASTENING</b>	Bolts with nuts on tops flanges, 12 rows each 12" c/c at front and 48" c/c all the way to the rear, 2 rivets per Apitong plank at each crossmember.
<b>SIDE RAILS</b>	3 3/4" x 5 13/16" high, extruded aluminum, Cargo Rail integrated.
<b>SIDE BOXES</b>	3 5/8" x 1 5/8" inside, 4" high, extruded aluminum. CMVSS-905 WLL, 5,500 lbs WLL approved.
<b>RUB RAILS</b>	Aluminum extrusions 3/8" x 2 3/4". Dual rub rail spacers 1" x 1 3/4" as anchor.
<b>CORNERS</b>	Bevelled.
<b>FENDERS</b>	Reinforcement over tires at rear, floor full length.
<b>KNEE BRACES</b>	1/4" formed aluminum plates, bolted in web and a crossmember, located each side.
<b>ENDS</b>	
<b>FRONT RAIL</b>	Bolted aluminum extrusion, 7" high, overlapped floor to allow floor plank to walk underneath.
<b>BUMPER</b>	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Aluminum, bolted uprights to frame, cross bar tubing 4" x 3/16" at a maximum height of 22" from under tubing to ground.
<b>BUMPER</b>	Aluminum plate, bolted between bumper uprights to close rear.
<b>BUMPER</b>	4 Heavy duty rubber dock, two at the end of rear rail and two on Uprights.
<b>REAR RAIL</b>	Aluminum extrusion, 6 1/2 high, 16000 lbs lift truck proof,



ITEM	DESCRIPTION
	including 3 boxes integrated.
<b>ELECTRICAL</b> <b>FRONT CONNECTOR</b> <b>ELECTRICAL SYSTEM</b> <b>MAIN SYSTEM</b>  <b>FLASHERS</b>  <b>TAIL LIGHTS</b>	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, (tail lights with male pins #54332, markers lights Micronova #47962, 47973, identification lights #47122 (2 1/2" dia.), licence light #60291-3). Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber. Sealed beams (Grote DEL #54332) red. Qty: 1 additional each side. Indicator lamp Tiremaax installed on road side front rail.
<b>LANDING GEAR</b> <b>SAND SHOES</b> <b>CRANK</b> <b>SPAN</b>	Holland, ATLAS 55 (LG442B). 10" x 10". Road side. Galvanized steel (G164)
<b>BOGIE</b> <b>BASIC MECANICAL</b> <b>BOGIE</b>	Basic mechanical for sales book. Fixed front suspension and slider bogie at rear painted Z frame structure, 6.5" R.H., with "UHMV" slider plastic pads, 4 retainers and 4 pneumatic locking pins, tandem 54", 65" and 122" spread.
<b>MECANICAL (GROUND AXLES)</b> <b>SUSPENSION</b> <b>SPRINGS</b> <b>AXLE(S)</b> <b>CAM SHAFTS</b> <b>TRACK</b> <b>DUST SHIELDS</b> <b>BRAKES</b> <b>BEARINGS</b> <b>SLACK ADJUSTERS</b> <b>SEALS</b> <b>BRAKE CHAMBERS</b> <b>HUBS AND DRUMS</b>  <b>RIMS</b>  <b>SPACERS</b>  <b>TIRES</b>	Hendrickson HT-250 (6.5"), tandem. Air. Hendrickson, HN-S505, 20,000lbs capacity. 28 splines. 77 1/2". None. 12 1/4" standard with Hendrickson H20-HXS linings. HM 218248 and HM 212049. Haldex, automatic, curved, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). Hub piloted wheel, 8 long studs, balanced cast drums outboard mount. Alcoa, aluminum, inside polished 17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts. Wheel guard 8 holes. Located between the inside wheel and the drum. Continental, 235/75 R 17.5 HTL-2 ECO-PLUS 18 ply (31.6") Automatic Tire inflation System Hendrickson Tiremaax.
<b>AIR SYSTEM</b> <b>GLAD HANDS</b> <b>AIR VALVES</b> <b>VALVE(S)</b>	Fixed. Rockwell Wabco, ABS, 2 sensors 1 modulator. Automatic blow down valve, WITHOUT control box,



ITEM	DESCRIPTION
<b>VALVE(S)</b> <b>AUTOMATIC TIRE INFLATION</b>       <b>AUTOMATIC TIRE INFLATION</b>	including glycerin filled pressure gauge in P.S.I. mounted in web of frame, to indicate load with a conversion table. Fast-brake kit. Automatic Tire inflation System Hendrickson Tiremaax <b>**PRO**</b> for a TANDEM, NOTE: Axles prep. fees included <b>*** Maximum allowable tire pressure for this device is 120psi ***</b>  "Automatic Tire Inflation Systems", REMARK: Make sure the system is adjusted to the same tires pressure written on the serial plate.
<b>ACCESSORIES</b> <b>REGISTRATION HOLDER</b> <b>MUD FLAPS</b> <b>EXTRA MUD FLAPS</b>  <b>SLIDING TRACK</b> <b>WINCHES</b> <b>CARGO HANDS</b> <b>CARGO HANDS RACK</b>	One plastic, Betts-PS-1 or equivalent. One set, rubber with Manac logo and vertical grooves to reduce spray. One set, rubber with Manac logo and vertical grooves to reduce spray, located at rear of slider axle. Full length, "LL" extruded aluminum, road side. Qty: 12, #49207-137-XZ, zinc plated slider (low profil 5 7/8"). Qty: 24, aluminum, for side rail with cargo rail. Qty: 2 , Rack (s) for cargo hands, bolted on one crossmember. (1 rack can hold 12 cargo hands) Located at (1) PER SIDE, STANDARD LOCATION
<b>FINISHING</b> <b>RETROREFLECTIVE TAPES</b>  <b>WHEELS OR RIMS</b>	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. Natural aluminum.
<b>ADDITIONAL OPTIONS</b>	REF U#162758 ESTIMATED EMPTY WEIGHT 10,700 LBS. +/- 3%

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.