

HALE TRAILER BRAKE & WHEEL

**KALYN
SIEBERT®**

Resale Inventory
A018975
VIN: 028015

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Trailer Model:

VersaMAXX

53 Feet Model

Ver. MAXX

53 Feet Model Standard Equipment

Net Capacity: 50 tons concentrated in 16 feet
Nominal: 53 feet OAL
8 feet 6 inches Wide

GOOSENECK:

Hydraulic Detachable Gooseneck 5 Position Adjustable Neck
50" Loaded 5th Wheel Height, 15" Setting, 2" King pin
Narrow neck, Chain storage rack under gooseneck
2" King Pin 84" Swing Radius
PTO powerent: two main & one lift ann cyfinders
Hydraulic Controls in a separate covered box
Front lugs provisioned for flip neck
Hydraulic connection on both sides of neck for winching operation

DECK:

Nominal Deck Length: 22.5 feet
Loaded Deck Height: 22 in 6 in Loaded Ground Clearance
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum
All 4 Beams same height & Beams are tapered like Paver Models
I-Beam Cross members on (approx.) 24" Centers
Junior I-Beam Cross members alternating - Outside bay only
1.5" Nominal Apitong Decking - Full Width, Secured by Floor Screws
D Rings: 9 Pairs - 6 Pair on the outside, 1 pair on each Bolster
Tie Downs & Chain Slots : Top Flange Outer beams 24" centers
Outriggers: 13 Pair Swing out + 1 Pair Heavy duty hook on at front
Front Flip Ramps (removable) for loading & AL Bogie Ramp: Manual raise
Two 6' AL Bus Ramps (Front/Rear Lugs included), Stored on neck

REAR SECTION:

Rear Deck 19 ft 7 in, Open Boom trough, brackets for Oversize Load Sign
Axles: Three , 5" round, 5/8" wall 25000# nominal capacity
Suspension: Ridewell or Equivalent air ride with Oil Seals
60" axle spacing, Open wheel wells, axle chains with cut off valves
Rear axle equipped with air lift, Auto Slack Adjusters
12-1/4" x 7-1/2" Air, Parking Brakes 1st & 2nd Axles, ABS: 2S1M
Hub: 8 Stud, Hub Piated, Long studs, Cast Drums
235/75R17.5, 16PR (Low Profile) radial tires
Aluminum Outer & Steel Inner Wheels Tire inflation system
Automatic/ Manual ride height control with dump valve & Air Gauge
Air Ride Suspension With 5 Position Ride Height

GENERAL:

12V System with 7 way, Modular Harness, LED Sealed Beam Lights
Strobe light package with toggle switch on rear
Epoxy Primer & Black Polyurethane Paint
Flag Holders - 2 Pairs - front deck and rear of trailer
Mid-Turn Signal/Clearance Light
Tool Tray: 4' expanded metal at front of deck (approx.)
Red & White Conspicuity tape
MS Mud Flaps
Winch: Two 15,000 lb. planetary hydraulic on neck & rear deck
100' of 1/2" wire rope & shackle, fairing rollers & cable tensioner
Four function wireless remote (controls both winches)
LED-Work lights on both winches with covered toggle switch
Battery Back-up w/ charger on rear for disconnected neck operation

Models

 53' Model

20,000 Lbs Winch (5/8" wire rope)

VersaMAXX Optional Equipment

Estimated Weight of the Equipment with the options :

22,810 lbs.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.