		SALES	RENTALS	PARTS	SERVICE
		Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
		Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
TRA	ILER	Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
BRAKE	& WHEEL	Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
		Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
		Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
ANDOL	A019033	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
SUPCE 1998	VIN: S018379	HaleTrailer	.com @hale	trailer f У	
in sinth		800-232	2-6535 *	FINANCING	AVAILABLE

Model Year - 2024LII

	Line 1	Model 440B-50CA	Description 440B-50CA - 50' Traveling Axle	Notes Qty 1
Operating and the system Operating and the system Operating and the system Operating and the system Operating and the system 1 Standard Equipment 1 Capacity - 80,000 Lbs. 1 Capacity - 80,000 Lbs. 1 Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe 10 Of Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Sase Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8'6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands 1	•	4400-3004		-
Other Concentration Other Concentration Obscription 1 Standard Equipment 1 Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. Deck Rating - 50,000 Lbs. Deck Rating - 50,000 Lbs. Deck Rating - 50,000 Lbs. Deck Rating - 50,000 Lbs. Deck Rating - 50,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options 1 Deck Width - 8" 6" Wide Deck (Standard) 1 Meavy Duty Gooseneck 1 1 Heavy Duty Gooseneck 1 1 Trailer Length - 52' Swing Clearance - 107" 1 Parking Stands 1 1	: <u>ar</u> H	•		
Description 1 Trailer Model - 440B-50CA 1 Standard Equipment Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, 0il Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21'' Pin Setting - 21'' Loaded Ground Clearance - 14'' at Bottom of Gooseneck Loaded Deck Height - 37'' Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16'' Centers Load Angle - 6.5 Degree Ease Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Heavy Duty Gooseneck 1 Heavy Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107'' Parking Stands 1				
Description 1 Trailer Model - 440B-50CA 1 Standard Equipment Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, 0il Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21'' Pin Setting - 21'' Loaded Ground Clearance - 14'' at Bottom of Gooseneck Loaded Deck Height - 37'' Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16'' Centers Load Angle - 6.5 Degree Ease Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Heavy Duty Gooseneck 1 Heavy Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Mary Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107'' Parking Stands 1				
Trailer Model - 440B-50CA 1 Standard Equipment Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands 1	Doscri	ntion		Qty
Standard Equipment Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' 1 Swing Clearance - 107" Parking Stands		-		
Capacity - 80,000 Lbs. Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107" Parking Stands	Ir	ailer Model - 440B-50CA		1
Deck Rating - 50,000 Lbs. in 10' Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8' 6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107"	Standa	ard Equipment		
Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107" Parking Stands				
Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107" Parking Stands		u		
Pin Setting - 21" Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107"			• • • • •	
Loaded Ground Clearance - 14" at Bottom of Gooseneck Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8' 6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands			Air Ride 22,500 Lb. Capacity	
Loaded Deck Height - 37" Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8' 6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands				
Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8' 6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands			4" at Bottom of Gooseneck	
 (10 Year Warranty) Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107" Parking Stands 		0		
Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) 1 Deck Width - 8' 6" Wide Deck (Standard) 1 Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands 1	-	-	D Clear Lens; Enhanced Stop, Turn, Tail and Ta	all; Rear Amber Strobe
Load Angle - 6.5 Degree Base Options Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard) Deck Width - 8' 6" Wide Deck (Standard) Heavy Duty Gooseneck Trailer Length - 52' Swing Clearance - 107" Parking Stands			bain Clats with Causes Stake Deckets on 16" (Contors
Toolboxes - Non-Load Bearing Top Opening Toolboxes (Standard)1Deck Width - 8' 6" Wide Deck (Standard)1Heavy Duty Gooseneck1Trailer Length - 52'5wing Clearance - 107"Parking Stands1			nam Siols with Square Stake Pockets on 16	centers
Deck Width - 8' 6" Wide Deck (Standard)1Heavy Duty Gooseneck1Trailer Length - 52'5wing Clearance - 107"Parking Stands1	Base O	options		
Heavy Duty Gooseneck 1 Trailer Length - 52' Swing Clearance - 107" Parking Stands 1	То	olboxes - Non-Load Bearing	g Top Opening Toolboxes (Standard)	1
Trailer Length - 52' Swing Clearance - 107" Parking Stands	De	eck Width - 8' 6" Wide Deck	(Standard)	1
Swing Clearance - 107" Parking Stands	He	eavy Duty Gooseneck		1
Parking Stands	Tr	ailer Length - 52'		
	Sv	ving Clearance - 107"		
Parking Stands - Jost 2 Speed (Standard) 1	<u>Parkin</u>	g Stands		
			(Standard)	1

Winch and Accessories				
Winch - 30K Ramsey, Planetary, 2 Speed with Air Release/Spring Tension				
Cable Roller Guide				
Upper Deck Slope Wear Protection - Wear Plate (Standard)				
Wireless Remote Control (6 Function: Tilt, Travel, and Winch)	1			
<u>Tie Downs</u>				
Lower Deck Center Keyhole Tie Downs Flush with Wood	1			
Deck and Accessories				
Spare Tire Carrier in Front Stake Pocket - Street Side	1			
Slope Mounted Dual LED Work Lights	1			
Folding Step(s) - Both Street and Curb Side (Galvanized)	1			
Skid Plates - Container Skid Plates Flush with Outer Flange (3/8"x6")	1			
Deck Type - 1-3/8" Apitong Wood Decking	1			
Strobe Lights In Bumper	1			
Suspension				
Scale System - Liquid Filled Air Pressure Gauge	1			
Tires and Wheels				
Tires - 235/75R 17.5 Double Coin (Standard)	1			
Outside Wheel Type - 17.5 Dura-Brite Aluminum Wheel (8 Bolt)	1			
Inside Wheel Type - 17.5 Steel Hub Wheel (8 Bolt) (Standard)	1			
Dexter Air Disc Brakes in lieu of STD	1			
Tire Air System - PSI Air Inflation System	1			
Paint and Special Options				
Standard Landoll Branded Decals (Affects Lower Deck Only)	1			
Anti-Slip Paint on Inner and Outer Flanges - Traction Paint on Inner & Outer Top Flange (Black)	1			
Hot Dip Galvanizing	1			
Hot Dip Galvanized Under Carriage Weldment	1			
Hot Dip Galvanized Bumper	1			
Paint over Galvanizing (Side Frame Web Only)	1			
Wet Paint Color - Black	1			

DISCLAIMER