

# HALE

## TRAILER

### BRAKE & WHEEL



Resale Inventory  
A019584  
VIN: 039803

#### SALES | RENTALS | PARTS | SERVICE

|                                |                               |
|--------------------------------|-------------------------------|
| Allentown, PA: 800-383-8894    | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500    | Portland, ME: 800-325-4253    |
| Concord, NC: 800-438-2250      | Raleigh, NC: 833-418-9777     |
| Delmar, DE: 866-486-1400       | Scranton, PA: 800-569-1400    |
| Des Moines, IA: 888-673-5011   | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127       | Voorhees, NJ: 866-315-0235    |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310     |

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

| STL 14-22 RD FRAMELESS            |  | WEIGHT 18767 lbs., +/- 3%, 51.5 cu. yds.                           |
|-----------------------------------|--|--|
| FLOOR                             | 35 ft .1 in. FLOOR LENGTH              | SERIAL NO. 5MADN3731HC039803                                       |
| LOAD PROFILE                      | MATERIAL, 80 GVWR                      | MODEL NO. TRAR37NFS600-2017  |
| LENGTH                            | 37 ft .0 in.                           |  |
| WIDTH                             | 102 in.                                |  |
| BODY TYPE                         | SINGLE PIECE                           |  |
| FLOOR                             | STD. 1/4" FULL                         |  |
| SIDES                             | SAME AS FLOOR (SINGLE PIECE)           |  |
| RADIUS BOTTOM                     | 22 in.                                 |  |
| CROSSMEMBER                       | 3-1/2" AR450 BOX ON 16" CENTERS        |  |
| FLAPS, REAR AXLE                  | STANDARD                               |  |
| FLAPS, FRONT AXLE(S)              | NONE                                   |  |
| VIBRATOR                          | NONE                                   |  |
| SIDES                             |  |  |
| WALL HEIGHT                       | 60 SOLID                               |  |
| TOP RAIL                          | 3/16" X 4" X 6" (STD)                  |  |
| TOP RAIL OPTION                   | SOLID                                  |  |
| BOLSTERS                          | 1, BOLSTER(s)                          |  |
| REAR POCKET SLOPE                 | 0 DEG.                                 |  |
| EXTENDED REAR POCKETS             | NO                                     |  |
| REAR POCKET HEIGHT                | 64.25, 3/16 GRADE 80                   |  |
| RAIN SKIRTS / 102" WIDE SUB-FRAME | NO                                     |  |
| REAR SKIRTS                       | 10 GA. STEEL OVER SUSPENSION, WELD-ON  |  |
| FRONT SKIRTS                      | NONE                                   |  |
| BULKHEAD                          |  |  |
| HOIST                             | 8-5-250 (35-38), CUSTOM                |  |
| REMOTE GREASE                     | NONE                                   |  |
| BULKHEAD TYPE                     | SLOPE NOSE (STANDARD)                  |  |
| DRIVER'S LADDER(s)                | STD. LADDER AT REAR                    | ADD FIXED LADDER TO FRONT OF BULKHEAD D.S. WITH ANGLE STEPS INSIDE |
| CURB SIDE LADDER(s)               | STD. LADDER AT REAR                    |  |
| TARP HOOKS                        | NO                                     |  |
| LIGHTS                            | 102 WIDE 0 0 0 0 0 0 0 0               |  |
| LIGHT TYPE                        | GROTE LED W/GROMMETS                   |  |
| LIGHT PANEL                       | (STANDARD) 3 LARGE-3 SMALL-3 LARGE     |  |
| LIGHT SHIELD/APRON                | (STANDARD) 3/8" X 4" FULL LIGHT SHIELD |  |
| 2-1/2" MARKER LIGHTS              | STANDARD. 3 EA. SIDE                   |  |
| MIDTURNS                          | (1) PAIR LED COMBO                     |  |
| BACK-UP LIGHTS                    | NONE                                   |  |
| REAR POCKET LIGHTS                | PAIR OF SMALL (MODEL 30)               |  |
| AUXILARY CABLE (4 OR 7 WAY)       | NONE                                   |  |
| GATE                              |  |  |
| GATE HEIGHT                       | 63 1/8 in.                             |  |
| GATE WIDTH                        | 94 in.                                 |  |
| GATE SHEET THICKNESS              | ALUMINUM SS GATE                       |  |
| GATE OPERATION                    | BALL VALVE (STANDARD)                  |  |
| HINGE TYPE                        | O. S. SWING C.S. W/ GROUND CONTROL     | USE AIR GROUND CONTROL   |
| COAL DOOR                         | NONE                                   |  |
| CHUTE                             | NONE                                   |  |
| BRACING                           | STD. (4 PANEL)                         |  |
| DOUBLE HANDLE DOOR                | NO                                     |  |
| 1/2 ROUND (SEAL) ON GATE          | NO                                     |  |
| ANGLE ON TOP OF GATE              | YES, 2 X 2 X 1/4                       |  |
| SPREADER CHAINS                   | NO                                     |  |
| WINDERS / SAFETY LATCH            | WINDERS (1) EACH SIDE (STEEL GATE)     |  |

| CHASSIS                       |  |                       |
|-------------------------------|--|-----------------------|
| MODEL                         | TRI-AXLE   |                       |
| SUBFRAME TYPE                 | 102in., WIDE I-BEAM , ALUMINUM                   |                       |
| PIN TO AXLE SETTING           | 404, 20 REAR SETTING                             |                       |
| SUSPENSION                    | HEND. INTRAAX AA-300 TP                          |                       |
| GALVANIZED SUSPENSION HANGERS | YES  |                       |
| SPRINGS                       | AIR  |                       |
| SUSPENSION CONTROL            | BALL VALVE (STANDARD)                            |                       |
| AXLE SPACING                  | 60 in.   |                       |
| AXLES                         | ( 3) AXLE FOR INTRAAX ONLY                       |                       |
| ABS                           | (1) 2S1M MERITOR / WABCO                         |                       |
| BRAKES                        | 7" XL, W/30-30 CHAMBERS                          |                       |
| SLACKS                        | STANDARD (GUNITE)                                |                       |
| CAM GUARDS (ALL AXLES)        | NONE   |                       |
| TIRES                         | (12) GENERAL S-371 11R 24.5 16 PLY               | RM 230 11R 24.5 16PLY |
| CHROME TOP HATS               | NONE   |                       |
| TIRE INFLATION SYSTEM         | HENDRICKSON SYSTEM ON ALL AXLES                  |                       |
| RIM TYPE (PER AXLE)           | ALCOA HP 24.5X8.25 10 HOLE 2 BUFFED 2 POLISHED   |                       |
| HUB AND DRUM                  | ( 6) CAST W/DURA L HUB. HP OB 10 STUD TP, LS, 7" |                       |
| SYNTHETIC LUBRICATION         | NO   |                       |
| HUBODOMETER                   | 24.5, TP, GREASE, BOLT-ON "STEMCO"               | OIL ILO GREASE        |
| DUST COVERS                   | NO   |                       |
| TIRE CARRIER                  | NONE   |                       |
| AIR GAUGE/SYSTEM              | YES, IN FRONT                                    |                       |
| AIR TANKS                     | 12" ALUMINUM AIR TANKS                           |                       |
| TOW/PINTLE HOOKS              | NONE   |                       |
| KING PIN SETTING              | 16   |                       |
| TRACTOR DRIVE MODEL           | TANDEM DRIVE                                     |                       |
| DOLLIES                       | (STD.) JOST A450 - 10 YEAR NO LUBE - D.S.        |                       |
| REGISTRATION HOLDER           | NONE   |                       |
| HYD. HOSE FITTING             | 1" X 120" HOSE W/WING FITTING                    |                       |
| DRAFT ARM TYPE                | 1/4 ALUMINUM                                     |                       |
| 5th WHEEL PLATE               | BREAK-AWAY PIN @ 48 in. HIGH                     |                       |
| ENCLOSURE FOR SWITCHES        | NONE   |                       |
| BUMPER                        | NONE   |                       |
| LIFT AXLE                     |  |                       |
| TYPE                          | NONE   |                       |
| NO. OF LIFT AXLES             | 0  |                       |
| LIFT KIT                      | (0) NONE   |                       |
| AXLE                          | NONE   |                       |
| TIRES                         | (0) NONE   |                       |
| RIM TYPE (PER AXLE)           | NONE   |                       |
| HUB AND DRUM                  | (0)  |                       |
| BRAKES                        | NONE   |                       |
| CONTROLS                      | NONE   |                       |
| FREE WHEEL VALVE              | NO   |                       |
| AXLE SPACING                  | NONE   |                       |
| TARP                          |  |                       |
| TARP MANUFACTURER             | NONE   |                       |
| TARP CONTROL                  | NONE   |                       |
| TARP COLOR                    | NONE   |                       |
| BOW HOLDERS                   | NONE   |                       |
| BOWS                          | NONE   |                       |
| TARP CENTER BRACKET           | NO   |                       |
| PAINT                         |  |                       |
| BODY COLOR                    | BLACK  |                       |
| CHASSIS COLOR                 | BLACK  |                       |
| "MAC" LOGOS                   | MAC BLACK  |                       |
| OPTIONAL SIGNS                | NONE   |                       |

#### DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.