

HALE TRAILER BRAKE & WHEEL



Resale Inventory

A019866

VIN: 62584

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 13.4 Units

STANDARD SPECIFICATIONS: CTSSF-45 (South Specs)

Type: Peerless dual axle, transport semi-trailer, **45 degree front**

Design: Box design, flat floor, end dump, live floor

Construction: **Skin stressed .063 prepainted black aluminum with aluminum exterior posts (14.5" centers), skins to be normal, last two (2) panels each side to be .125 black aluminum (furnished by customer), skins to be "standard design"**

Top Rail: **Refuse "Enclosed style" top rail**

Bottom Rail: **1/4" extruded aluminum**

Unloading Time: Approximately 8 minutes

Capacity: 13.4 units (99.3 cu yd) (at top of bows)

Dimensions: **45' long, 8'6" wide, 12'10" high (at top of arched bows), 37" king pin location, 36" rear axle from rear of trailer**

Tires: **Eight (8) 11:00 x 22.5 General RA radial tires (16 ply)**

Wheels: **Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount**

Axles: **25,000# cap., HP spindles, 77.5" track, 10stud, 11 1/4' B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks, enclosed brake cams**

Brakes: **16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system**

A.B.S.: 2 sensor - 1 module

Suspension: **Ridewell RAR 266 air ride with slider suspension, (50,000# cap.)**

Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**), channel bracing

King Pin: Standard SAE, heat treated, **37" setting, 49" height, 3 I-beams with 1/2" plate**

Cross Sills & Decking: **KEITH #2190 SLATS WITH 3.5" DRIVE** two live floor, **4" Jr. I-Beams on 12" centers and 8" centers over suspension with aluminum sub-deck, Hale to furnish and KNL Holdings will install the floor kit**



Hydraulic Lines: **Stainless steel hydraulic lines**

Top: Flat design, open top, **three (3) "Refuse style" center ties (6" arch)**

Top Cover: **Shur-lok roll over tarp, black in color, rear crank, Flex-handle and telescoping pole, handles on both sides – steel door frame**

Rear Door: Full opening, **side hinged, solid freight door with four (4) latches, low mount**

Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **None**

Ladders: **One located at front with safety loop and NO REAR LADDER**

Rope Hooks: None

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights, **all lights to be LED**

Back-up Lights: **Mounted in bumper between the bumper blades – wire to be ran to headboard**

Work Lights: **Mounted inside front of trailer under the top rail – wired to a toggle switch on headboard**

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted BLACK**

Weight: Approximately 14,730#

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.