

  <b>Resale Inventory</b> <b>A019927</b> <b>VIN: 033231</b>	<b>SALES   RENTALS   PARTS   SERVICE</b>			
	<b>Allentown, PA:</b> 800-383-8894 <b>Baltimore, MD:</b> 888-601-7500 <b>Boston, MA:</b> 800-854-5310 <b>Concord, NC:</b> 800-438-2250 <b>Delmar, DE:</b> 866-486-1400 <b>Des Moines, IA:</b> 888-673-5011 <b>Elkton, MD:</b> 800-544-7127	<b>Jacksonville, FL:</b> 800-828-3055 <b>Little Rock, AR:</b> 833-424-8944 <b>Portland, ME:</b> 800-325-4253 <b>Richmond, VA:</b> 866-839-3495 <b>Scranton, PA:</b> 800-569-1400 <b>Springfield, MA:</b> 800-854-5306 <b>Voorhees, NJ:</b> 866-315-0235	<b>HaleTrailer.com   @haletrailer</b>     	
<b>800-232-6535</b> *FINANCING AVAILABLE				

**Model:** 35HT

**Capacity in tons:** 35

Gooseneck Design	Fixed Perimeter Frame Design
Upper Deck Length	9'-2"
Loaded 5th Wheel Height	49"
Swing Radius	76"
Planetary Winch	12,000# With 60'-0" of 1/2" cable Winch located top, center, front of gooseneck Cable roller at rear center of gooseneck
Power Source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Electrical Receptacle	Seven pin connector
Tool Box	On front of gooseneck, driver's side
Landing Gear	Two (2) speed with crank on driver's side
Headboard	None
Platform	Covered with 1/4" floor plate Three (3) stake pockets with fore and aft chain slots each side Four (4) stake pockets across front of platform
Winch Remote	Two (2) function wireless remote for winch operation
Additional gooseneck Specifications	None
Deck Section Design	Perimeter Frame
Deck Section Length	30'-0"
Deck Section Width	8'-6"
Crossmembers	Heavy duty I-beam crossmembers on 12" centers
Loaded Deck Height	36"
Loaded Ground Clearance	20"
Flooring	1-1/2" apitong
Stake Pockets	Stake pockets with fore and aft chain slots each side of deck on 2'-0" centers
Deck to Gooseneck Ramp	8'-0", 13.3 Degree hydraulically operated full width deck ramp with 1-1/2" apitong Deck locks in raised position automatically with an over center lock

---

Additional Deck Specifications	None
Number of Axles	2
Axle Spacing	50"
Axle Capacity	25,000#
Brakes	12-1/4" x 7-1/2" S-cam air actuated with spring brakes on all axles
Anti-lock Brake System	Two (2) sensor, one (1) modulator system
Wheels	Eight (8) stud; 6.75 x 17.5 steel disc hub piloted system with oil seals
Tires	Eight (8) 235/75R17.5 (H) 16 PR radials
Wheel Well Covers	3/8" Floor plate over tires
Suspension	Air ride
Exhaust Valve	Manual
Suspension Options	None
Length	8'-7" Folded length 12'-0" Extended length
Load Angle	14.5 Degrees
Lift Capacity	20,000# Centered 4'-0" behind hinge pin
Flooring	1-1/2" apitong on 8'-0" section 1/4" Floor plate on 4'-0" section
Stake Pockets	Four (4) stake pockets with fore and aft chain slots each side 8'-0" section
General	Tail is equipped with automatic locking device and self cleaning bushings
Lash Rings	Four (4) lash rings each side of gooseneck Lash rings on 4'-0" centers on lower deck and 8'-0" tail section
Lights and Wiring	12 Volt L.E.D. lights, including mid-turn, excluding license plate light
Paint	Talbert standard black
Estimated Empty Weight	15,850#
Design	Over all length: 48'-0" Capacity: 70,000# Distributed, 50,000# in 16'-0" @ 60 MPH
Additional General Specifications	None

---

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.