

HALE

TRAILER

BRAKE & WHEEL

**KALYN
SIEBERT®**

A020151
VIN: 132416

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Trailer Model:

Kalyn Hydraulic Sliding Axle KS-HSA-2A-40T-50

KS-HSA-2A-40T-50 Standard Equipment

Net Capacity: 40 Tons
Nominal: 50 foot OAL
8 feet 6 inches Wide

80,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft
Kingpin to center of rear axle 40 feet in Transport Mode

Dump angle 16° Loading angle 7°

GOOSENECK:

10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')
48" Loaded 5th Wheel Height, 18" Kingpin Setting
86" Swing Radius (48' & 50') / 96" Swing Radius (53')
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable
Work lights on the winch 2 Tool compartments
Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings
Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door
2-Speed Landing Gear, Crank Handle Roadside

SUSPENSION:

25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles
50" axle spacing 71" track
12-1/4" x 7-1/2" Brakes ABS Module: 2S1M
Auto Slack Adjusters and Spring Brakes on all Axles
6.75 x 17.5 Hub Piloted Disc Wheels
235/75 R 17.5 16PR Tires Manual Dump Valve
Suspension: Ridewell or Equivalent Air ride Air Ride
Alignment Bracket for Sliding Suspension

DECK:

Nominal Deck Length: 39.34 feet
Nominal Deck Width: 102 in
Loaded Deck Height: 37 in
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum
14" tall main beams and 15" tall side rails
4" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck (full width)
Double Key Hole Chain Slots in Upper Flange on 36" Centers
Double Key Hole Chain Slots Along Center of Deck on 36" Centers
Reinforced Rear Approach Plate with 6 Chain Slots
Cable Roller Centered at Front of Lower Deck

GENERAL:

12 Volt System with 7 way Sealed Harness
DOT Rubber Mounted Sealed Beam LED Lights
Epoxy Primer & Black Polyurethane Paint
2 Function Wireless Remote for Winch
Heavy Duty DOT Approved Bumper
Red & White Conspicuity tape KS Mud Flaps
3 LED marker lights each side including mid turn
Strobe light with toggle switch on rear

Additional Features:

2 axle, 40 Ton, 50' Model
6 Function Wireless Remote
OEM 235/75R 17.5 16 PR Tires
AirWeigh Load Scale
Tire Inflation
Central Lube - 18 point manual
19,226 LBS

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.