

Model:AC3-25 (air)Capacity in tons:25

Pintle eye	Adjustable pintle eye (3" I.D.) with 48" chain and grab hooks
Tongue	5'-6" with lockable tool box with aluminum diamond plate lid
	Note:
	Move tool box hinge 4" forward
Landing Gear	2-speed, 50,000# crank down dual landing leg, mounted to main beams and
C	headboard
Electrical receptacle	Seven pin connector
Headboard	8" high full width
Deck section design	One piece tongue, main beam and beavertail (cold formed)
Deck section length	30'-0" (24'-0" flat with 6'-0" beavertail)
Deck section width	8'-6"
Loaded deck height	32-3/4"
Flooring	1-1/2" apitong with individual steel floor plate wheel covers
Lash rings	10 total -
	4 each side on flat deck (straight style), 8 total
	1 each side on beavertail (straight style), 2 total
Cross members	6" deep hi-tensile
Main beams	12" deep hi-tensile
Side members	8" deep hi-tensile
Beavertail	6'-0" Double break with wood flooring full width
Ramps	5'-0" with wood flooring with 3 springs per ramp and grab handles
Number of axles	3
Axle capacity	25,000#, full width track axles
Brakes	12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on axle 2 & 3.
Wheels	Steel disc with oil seals (6.75 x 17.5)
Tires	Twelve (12) 215/75R17.5 (H) 16PR radials
	Use valve stem extensions on inside wheels
Suspension	1) First axle air ride equipped with air lift axle
	2) Air lift control located in toolbox
	3) 44,800# Hutch spring on axle 2 & 3
Lights and wiring	12 volt LED system (license plate regular), supplied with female 7-way plug on
	tongue, SUPPLY JUMPER CORD FOR TRUCK
Paint	Valspar standard Talbert black, R-Cure 800 series paint
Additional general specifications	Formed step in front of 1st axle both sides of trailer
	•

DISCLAIMER