

TIPPER SP

Model # TNSP48FR1000

Weight 14070 lbs. *** C	Cubic Yards 116	
BODY		
LOAD PROFILE	MATERIAL, 102K GVWR	
LENGTH	48	
WIDTH	102	
FLOOR	1/4 IN. W/ 3/8 IN. LAST 24 FT. (48FT OR ABOVE LENGTH TRAILER	
)	
CROSSMEMBER SPACING	5 1/4 IN. x 8 IN. U CROSSMEMBERS, 10 IN. SPACE	
RUBBER SEAL	YES	
WALL HEIGHT	100	
WALL THICKNESS	0.19	
1/4 IN. WALL LAST 15 FT.	NONE	
WALLLINER	NONE	
TAPERED SIDE	NONE	
FULL LID	NONE	
TOP RAIL OPTION	6 IN. W X 9 IN. T X 5/8 IN.	
6 IN. W X 9 IN. T X 5/8 IN.		
NO. OF UPRIGHTS	20	
NO. OF UPRIGHTS TO ADD OR SUBTRACT	0	
HORIZONTAL BRACING	NONE	
TARP BAR	YES, SINGLE	
BULKHEAD	3/16 IN.	
BULKHEAD STEPS	CATWALK & LADDER W/ STEPS INSIDE	
SIDES STEPS D.S.	NONE	
SIDES STEPS C.S.	NONE	
FRONT FENDERS WITH FLAPS	NONE	
BOTTOM RAIL	CLEAN-OUT	
UPPER CROSS TUBES / CAPS	(1) SPRING-MID	
TIRE CARRIER	NONE	
LIGHTS		
LIGHT TYPE	GROTE L.E.D. W/ GROMMET	

LIGHIS	
LIGHT TYPE	GROTE L.E.D. W/ GROMMET
LIGHT PANEL	3 LARGE - 3 SMALL - 3 LARGE
APRON	3/8 IN. X 1-1/2 IN. FULL LIGHT SHIELD
STD. MARKER LIGHTS	(3) EACH SIDE
MID-TURNS	(1) PAIR L.E.D. BRACKET
BACK-UP LIGHTS	NONE
AUXILIARY CABLE	NONE
REAR POCKET LIGHTS	1 PAIR

GATE SHEET THICKNESS	SMOOTH SIDE PANELS
GATE OPERATION	BALL VALVE
HINGE TYPE	OVERSLUNG ONLY
GATE BRACING	NO BRACING (SMOOTH SIDE PANELS)
WINDERS / SAFETY LATCH	WINDERS (1) EACH SIDE
GATE STEPS	UP CENTER OF GATE OUTSIDE ONLY
TARP HOOKS	BULKHEAD AND GATE

PRIMARY AXLES	
MODEL	CLOSED TANDEM
NO. OF PRIMARY AXLES	2
SUSPENSION	MAC FABBED GALVANIZED SINGLE LEAF TAN. (49)
AXLE SPACING	49
SUB-FRAME	TANDEM 10 IN. I-BEAM (ALUM)
AXLES	TP 77.5 5/8W AXN WABCO 7" 25K
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS	NONE
HUB AND DRUM	CAST W/ STEEL HUB HP 10 STUD TP, LS, 7 IN.
TIRES	GENERAL RA 11R 22.5 16 PLY
WHEELS	STEEL HP 22.5X8.25 - WHITE POWDER COATED
PRIMARY AXLE TIRE INFLATION SYSTEM	MOVED TO CHASSIS

LIFT AXLES

NO. OF LIFT AXLES	0
LIFT AXLE SUSPENSION	NONE
LIFT KIT	NONE
LIFT AXLE DISTANCE	N/A
LIFT AXLE	NONE
LIFT AXLE BRAKES	NONE
LIFT AXLE CAM GUARDS	NONE
LIFT AXLE HUB AND DRUM	NONE
LIFT AXLE TIRES	NONE
LIFT AXLE WHEELS	NONE
LIFT AXLE CONTROLS	NONE
FREE WHEEL VALVE	NONE
LIFT AXLE TIRE INFLATION SYSTEM	MOVED TO CHASSIS

STEERABLE LIFT AXLES

NO. OF STEERABLE AXLES	0
STEERABLE AXLE SUSPENSION	NONE
STEERABLE AXLE DISTANCE	N/A
STEERABLE AXLES	NONE
STEERABLE AXLE BRAKES	NONE
STEERABLE AXLE HUB AND DRUMS	NONE
STEERABLE AXLE TIRES	NONE
STEERABLE AXLE WHEELS	NONE
STEERABLE AXLE CONTROLS	NONE
STEERABLE AXLE LIFT KIT	NONE

8 LOW PROFILE
IN. HIGH
CLUDED W/ SUSPENSION
DNE
) 2S1M MERITOR / WABCO
JTOMATIC
DNE
/NTHETIC GREASE
DNE
DNE

DOLLIES - LANDING GEAR - LANDING LEGS	JOST H451 - (62,500 LB.) - 10 YEAR NO LUBE - GALVANIZED STEEL
	- D.S.
REGISTRATION HOLDER	NONE
AIR GAUGE / SYSTEM	NONE
ENCLOSURE FOR SWITCHES	NONE
AIR TANKS	ALUMINUM TANK
FLAPS FRONT OF TIRES	NONE
FLAPS REAR OF TIRES	FLAP BEHIND REAR AXLE
BUMPER	STANDARD GALV. STEEL PUSH BLOCKS
TOW RINGS	NONE
TIPPER PLATFORM BACKSTOP HEIGHT	40 IN (UNLESS NOTED)
TIPPER PLATFORM LENGTH	38 FT

TARP

TARP MANUFACTURER	NONE	
TARP CONTROL	NONE	
TARP COLOR	NONE	
BOW HOLDERS	NONE	
TARP BRACKET	NONE	

PAINT	
SUSPENSION COLOR	BLACK SOFT COAT
PIN STRIPING	BLACK (931716)
MAC MACHINE FINISH LOGOS	BLACK (931716)
OPTIONAL SIGNS	NONE