




Resale Inventory
 A020283
 VIN: 120266

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
LENGTH WIDTH HEIGHT	48'-0" 102", 97" between side rails. Floor, approximately 60" high at front and 54" at rear. 
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	5/16", plug welded structure. 30" from front. 48".
STRUCTURE FLANGES WEB GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES RUB RAILS CORNERS X BRACES	Frame with "CAMBER". 3/8" x 5", 100 000 psi steel. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 26" high at the peak with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre. Apitong, 1 1/8" thick shiplap finished, no preservative. One screw per plank, staggered, at each crossmember and 2 screws at ends. Formed channel 6" @ 4.6 lbs/ft. Made of 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (US Dimensions). 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
ENDS FRONT RAIL BUMPER HEADBOARD	9 gauge formed steel. D.O.T. approved, (or in accordance with regulations) uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, (tail lights with male pins #53252, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M). Sealed beams LED, (Grote #53963), one lamp including side marker and flasher, each side at middle point, amber.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V. 10" x 11 1/2". Road side.
BOGIE BOGIE SUSPENSION	Slider, air ride suspension, tandem, 50" spread. Bogie "Z" frame for suspension with 14" mounting height. (48" travel) Hendrickson HT-230T, tandem, 50" spread.



ITEM	DESCRIPTION
U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	With nuts at top. Air. Meritor, TQ 467_L, 21 900 lbs. capacity. Welded. 28 splines, with bolt-on bushing. 77". Steel, bolted. 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). KIC, 10 stud disc hubs, drums 114 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single steel or aluminium wheels. Accuride, 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Bridgestone, 11 R 24.5 R-196 14 ply (43.3")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE DIAGNOSTIC CABLE	Fixed. Rockwell Wabco, ABS, 2 sensors 1 modulator. Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. not included with ABS valve.
ACCESSORIES REGISTRATION HOLDER WINCHES STRAPS SLIDING TRACK MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, #649390, zinc plated, slider (5"). Qty: 12, nylon, with 1'-6" chain and grab hook, 30' long x 3" wide. Full length, "C" shaped steel, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of epoxy primer and two lux-o-thane top coats, Color: black, code: Sico 569-183. Black. White. Conspicuity striping in compliance with CMVSS 108. Gray and red, 2' segments each side, fully covers rear sill and horizontal underride protection bar.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.