

HALE TRAILER

BRAKE & WHEEL



Resale Inventory

A020377

VIN: 141001

HT Original®

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

DRY FREIGHT EXTERIOR SKIN 53'

		GEOMETRY	OPTION	
LENGTH EXTERIOR.	53' 0"			
-INT.	52'-6"			
WIDTH -EXT.	102.36"			
-INT.	98.75"			
HEIGHT -EXT.	13'-6"			
-INT.	110"			
UPPER COUPLER HT.	47"			
KING PIN LOCATION	36"			
TIRES				
TYPE	MICHELIN XTA X-ONE		X	
SIZE	445/50 R 22.5 (G)		X	
ROOF				
ROOF SHEET	.075" KEMLITE ETR TRANSLUCENT		X	
ROOF BOW TYPE	ALUMINUM		X	
ROOF BOW SPACING	16" CENTERS FULL LENGTH		X	
FRONT				
CORNER RADIUS	6" ALUMINUM			
FRONT SHEETS	.050" PPW ALUMINUM			
FRONT UPRIGHTS	(4) 3.20" DEEP STL HATS WELD TO U.C.		X	
GLADHANDS	PHILLIPS QWIK-E W/FILTERS MOUNTED IN RECESSED PAN		X	
REG. CARDHOLDER	BETTS PS-1 ON LOWER ROAD SIDE FRONT		X	
SIDEWALL				
SIDE MATERIAL	.050" PREPAINTED WHITE ALUMINUM			
SIDE UPRIGHTS	1.13" DEEP ALUMINUM HAT POSTS		X	
UPRIGHT CENTERS	12" CENTERS THROUGHOUT		X	
FORWARD & UPPER COUPLER AREA				
UPPER COUPLER	3.40" JOGGLED W/ 52.25" EXPOSED. PRIME PAINTED ONLY.			
APPROACH PLATE	.25" THICK 80,000 LB YIELD. 2 EXTRA LONGITUDINALS			
BOTTOM MAINBEAM PL	.25" THICK 80,000 LB YIELD			
FORWARD XMEMBERS	HAT SHAPED: U.C. TO SUPP. GEAR			
SUPPORT GEAR	JOST 401G317 W/CROSSMEMBERS ON 8" C/L		X	
SHOES	10" X 10" LOW PROFILE CUSHION FOOT			
LOCATION	95" C/L SUPP. GEAR TO C/L KING PIN		X	
CRANK HANDLE	ROADSIDE			
BAY AREA XMEMBERS	4" ALUMINUM I-BEAMS		X	
XMEMBER CENTERS	BAY: 8" C/L & FORWARD AREA: 10" C/L		X	
TIRE CARRIER	NONE			
UPPER RUNNING GEAR AREA				
U.R.G. XMEMBERS	3" STEEL I-BEAMS		X	
XMEMBER CENTERS	8" C/L		X	
U. R.G. RAILS	216" RAIL LENGTH (65"-169")			
SLIDER ASSEMBLY	HOLLAND ULTRA LITE 2		X	
MUDFLAPS	PLASTIC W/ HYUNDAI LOGO			
LOWER RUNNING GEAR AREA				
SUSPENSION	HOLLAND ULTRA-LITE 2 (2" OFF SET)		X	
SPRINGS	MERITOR SIMILAIR COMPOSITE SPRING		X	
BRAKE SYSTEM	SEALCO #110500 VALVE W/WABCO 2S/1M ABS			
CHAMBERS	TSE 3030 TAMPER RESIST			
BRAKES	16.5" x 7" MERITOR MA212			
AXLES	MERITOR TP4670Q .50" WALL 77.50" TRACK FOR 2" OFF SET 'P' SPINDLE			



HT Original®

DRY FREIGHT EXTERIOR SKIN 53'

DEALER:	HALE TRAILER BRAKE & WHEEL		
LOWER RUNNING GEAR AREA			
BRAKE ADJUSTERS	GUNITE AUTO - 5.50"		
HUB & DRUM	10 STUD HUB PILOTED OUTBOARD MTD CENTRIFUSE DRUMS P' SPINDLE	X	
WHEELS	22.5 x 14.00 ACCURIDE ALUM DISC (MILL FINISHED)	X	
OIL SEALS	STEMCO PLATINUM PERFORMANCE SYSTEM OIL FOR P' SPINDLE		
HUBODOMETER	NONE		
REAR			
HEADER	2" SHALLOW HEADER (110" DOOR OPENING HEIGHT)	X	
REAR DOOR TYPE	.50" XXENTRIA COMPOSITE	X	
REAR DOOR MAT'L	COMPOSITE	X	
LOCK RODS	BLOXWICH, 1 PER DOOR WITH MID-CAM LOCK	X	
HINGES	ALUMINUM, 4 PER DOOR		
UNDERRIDE PROTECTIO	4" x 4" TUBE. HOT DIPPED GALVANIZED STEEL		
RUBBER BUMPERS	NONE	X	
LINING			
SIDE LINING	1 ROW X 12" HIGH HD. EXTRUDED ALUM SCUFF (NOMINAL 3/16") AT FLOOR LEVEL WITH 4 ROWS X 12" HIGH - TOTAL 48" HIGH STANDARD DUTY (NOMINAL 1/8") CORRUGATED ALUM SCUFF IMMEDIATLEY ABOVE FIRST ROW, TOTAL 60" HIGH EXTRUDED ALUM SCUFF. .060"-.050" BULLITEX REMAINDER. LINING MUST BE "TUCKED" BEHIND SCUFFBAND	SEE NOTE	Rev. 1
SIDE SCUFFBAND	NONE	X	
NOSE LINING	1 ROW X 12" HIGH HD. EXTRUDED ALUM SCUFF (NOMINAL 3/16") AT FLOOR LEVEL WITH 4 ROWS X 12" HIGH - TOTAL 48" HIGH STANDARD DUTY (NOMINAL 1/8") CORRUGATED ALUM SCUFF IMMEDIATLEY ABOVE FIRST ROW, TOTAL 60" HIGH EXTRUDED ALUM SCUFF. .060"-.050" BULLITEX REMAINDER. LINING MUST BE "TUCKED" BEHIND SCUFF BAND	SEE NOTE	Rev. 1
FRONT SCUFFBAND	NONE		
CEILING LINING	NONE		
FLOOR			
FLOOR	1-3/16" HAVCO COMPOSITE	X	
FLOOR SCREWS	(3).31" DIA.SCREWS/BOARD/XMBER		
THRESHOLD PLATE	.13" X 20" STL DIA.PLT. PRIMED	X	
ELECTRICAL			
LIGHTS	SEE ITEM # 4	X	
MID-TURN SIGNAL	SEE ITEM # 4	X	
ELECTRICAL CONN.	PHILLIPS 7-WAY WITH CIRCUIT BREAKERS	X	
LOCATION	MOUNTED IN RECESSED PAN ON LOWER ROADSIDE FRONT	X	
PAINT & FINISH			
UNDERCARRIAGE	BLACK UNDERCOATING		
CHASSIS &SUPP GEAR	GRAY		
REAR FRAME	HOT DIPPED GALVANIZED STEEL REAR FRAME & BUCKPLATE		
WHEELS	MILL FINISHED ALUMINUM	X	
DECALS	CONSPICUITY TAPE - HYUNDAI LOGO TYPE - SIDE TAPE TO BE MOUNTED ON SIDE SHEETS		
INSPECTION DECAL	FHWA INSTALLED		
TEMP LIFT PADS	NONE		

- 1 TEMPORARY LICENSE PLATE FOR TRANSPORT. FASTEN WITH NUT & BOLT
- 2 Hot Dipped Galvanized Support Gear Bracing and Wing Plates
- 3 Rear lower side marker lights to be approx. flush with bottom rail.
- 4 All marker lights to be Grote #45812 & 45813 except for rear header lights which are #46922 LED. All marker lights mounted on #43690 bracket. Locate lights 2 upper front rail & 2 upper side rail, beneath bottom rail on bracket at center, beneath bottom rail on bracket at rear. Install bracket with 2 screws. Bottom rail center light to be wired as combination marker & turn signal. Grote Stop, Tail, Turn signals
- 5 Meritor PSI Tire Inflation System
- 6 Delete rubber door stops on rear doors.
- 7 Install rear door hinges with camtainers to allow doors to open as close to sidewall as possible
- 8
- 9 Rear dock Height not to be less than 47".
- 10 Note: Bullitex lining to be screwed and glued to uprights. Screws to be as flush as possible to lining so not to snag cargo
- 11 Stainless Steel front impact guard with stainless steel impact striker angle
- 12 Install **Customer Furnished** unit numbers inside and outside. Location to be determined per **Customer Furnished Schematic**
- 13

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.