

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A020551
VIN: 575740

SALES | RENTALS | PARTS | SERVICE

| | | | |
|------------------------|--------------|--------------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

| Renegade LXTN40 34-60 Air Tandem (Model: RENEGADELXTN40) | |
|--|--------------------------|
| | Est. Wt.: 23,765# +/- 3% |
| Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads | |
| Load Base: 16-foot rigid 2-point load centered in deck | |
| Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs | |
| Compatibility: Designed to accept 3rd flip axle - none | |
| Length / Width: 50 feet 1 inch - 102 inches wide | |
| Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation | |
| Loaded Fifth Wheel Height: 50 in nominal loaded fifth wheel height with 5 ride height positions | |
| Power Source: None | |
| Electrical Receptacle: J560 7-pin connector | |
| Deck Design: Flat level telescopic deck design | |
| Deck Length: 34 feet 0 inches clear deck length (retracted) - 60 feet 0 inches (extended) ** Note trailer overall length is 55 feet | |
| Loaded Deck Height: 20 inches with 6 inches ground clearance | |
| Flooring: 1 3/8 inch nominal wood (full width) | |
| Recessed Floor Mounted D-Ring Package: None | |
| Crossmembers: On 24 inch centers | |
| Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats | |
| Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type | |
| Front Bogie Ramp: Sloped steel bogie ramp (full width) | |
| Mini Boom Trough & Traction Cleats: None | |
| Deck to Bogie Connection: Fixed | |
| Number of Axles: 2 | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 54.5 inches spread (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Dust Shields: None | |
| Spring Brakes: Spring brakes on 2 axles | |
| Suspension: Air ride with automatic controls | |
| Tires: 255/70R 22.5 H ply OEM Standard | |
| Wheels: 8.25 x 22.5 steel disc - hub-piloted | |
| Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor | |
| Rear Bogie Height: 41 inches | |
| Bumper: 3 tail light package | |
| Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears | |
| Width: 8 feet 6 inches | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes | |
| Flip Axle: None | |
| Dust Shields on Flip Axle: None | |
| Paint: Fontaine black polyurethane enamel | |
| Lash Rings: 12 pair - 24 total | |

| | |
|---|--|
| Flag Holders: 2 pair flag holders | |
| ABS: 4S/2M system without diagnostic tool and cable | |
| Liquid Filled Gauge: Included | |
| Marker Lights: 8 marker lights per side including mid-turn | |
| Accent Package: Stainless steel bumper insert | |
| VIN Plate: Bilingual VIN plate | |
| Registration/Document Holder: Install registration/document holder | |

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.