

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A020845
VIN: 524402

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Revolution 52 Alum Flat 48' Wide Spread Air (Model: HCR5212WSA)	
	Est. Wt.: 8,920# +/- 3%
Length / Width: 48 feet x 102 inches	
Suspension Type: Wide spread air	
Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads	
Flooring: Knurled extruded 3-1/8 aluminum, multi-hollow friction stir welded floor with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear	
Side Rails: Exclusive Revolution Technology – one piece routed aluminum designed for strength and impact	
Stationary Chain Cargo Tie Downs: 15 pair - recessed in siderails	
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)	
Rubrail: Integrated with side rail	
Main Beams: Extruded aluminum - 8.25 inch flange	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: Jost A400G19 with forward & rear bracing	
Bulkheads: None standard	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks; Steel air tank	
Air Line Filters: *None installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 122 inches - set at rear	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: *** 3-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc pre-painted GRAY Maxion Lightweight #10073	
Tires: 295/75R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson AANT23K Intraax air ride	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: *Not installed	
Front Corners: Tapered	
Electrical System: Exclusive Revolution Technology: LED: 5 lights/side, 3 rear recessed light bars, with 10 Year Comprehensive Electrical System Warranty	
Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections	
Paint: Black urethane on steel parts with Revolution decals	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Meets U.S. underride requirements	
Mudflaps: 1 set OEM standard	
Spare Tire Carrier: None standard	
Winch Track: Dual full-length integrated aluminum – double L design	
Sliding Winches: 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers	
Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: None standard	
Tool Box: None standard; Tool box mounting brackets installed road side between spread axles to accept (1) 24" x 24" x 60" tool box: Tool box not included*	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.