



A020850 VIN: 000273

## <u>SALES | RENTALS | PARTS | SERVICE</u>

Allentown, PA: Jacksonville, FL: 800-383-8894 800-828-3055 Baltimore, MD: Little Rock, AR: 888-601-7500 833-424-8944 Portland, ME: Boston, MA: 800-854-5310 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer (f) (s) (m) (o) (m)

800-232-6535 \*FINANCING AVAILABLE

## 30NTT 30 Ton Tridem Non Tilt Tags

Base Weight: 11,

11,820

TRAILER

Overall Length \*NPO\*: 34 ft. 7 in.

Overall Width 102 in.

Weight lbs +/- 2% 12464, including options

A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam

Hitch 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

DECK

Deck Length \*NPO\*: 22 ft.

Loaded Deck Height 34 in.

Main FrameHi-Tensile Wide Flange 14 in. @ 26Cross MembersHi-Tensile 6 in. Channel @ 8.2

Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside

Floor 1 3/4 in. Hardwood
Landing Gear Dual 2 Speed

**Step** Bolt on, Located on Front Corner of deck, Driver side

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track

Spread 49 in.

SuspensionHeavy Duty spring rideBrakesQuick Change 12 1/4 in. x 7 in.

Brake Chamber #3030, All Axles

Air Brake System 2S/1M
Air Tank(s) Aluminum
Bearings Oil Bath
Slack Adjusters Automatic

Hubs & Drums 8 Stud Unimount C / W Cast Drums

**Tires** 235/75R17.5 16 ply

Wheels Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL

**Length** 5 ft. @ 10 degree slope, Planked in

RAMPS

**Length** \* 38 in. x 76 in. Wood Filled Air Operated Ramp

**GENERAL SPECIFICATIONS** 

**Electrical System** Modular, Vapor Proof GROTE Ultra Blue

Lights LED CMVSS 108 / FMVSS 108

Lights Amber Flashing Strobe Lights(Mounted in Ramps)

Front Connector SAE J560 7 Pin

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Color Black

Mudflaps 1 set of BWS at rear

## 30 Ton Tridem Non Tilt Tags GENERAL SPECIFICATIONS Toolbox Full A Frame mounted with solid bottom and cover Load Securement 7 pair of D-rings Fenders 3/16 in. deck plate GVWR Rating is based on standard configuration and a 15% Tongue weight distribution