



Resale Inventory
A020858
VIN: 856404

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055
 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944
 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253
 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495
 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400
 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306
 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE



Fifth wheel height : 48

King Pin Other : 28.5
Location : Bolt-on

Coupler
Plate: 1/2" HTS

Gooseneck: Hinged

Frame : Extendable with camber

Extendable boxed beams (caisson): 3+1

Removable blade support on beams: 1

X-Member : Fabricated special

Nose corners : 45°

Side Rail :

Rub rail : None

Stake pocket : None

At front bolster : N
 At rear bolster :

Winches : None

Sliding track :

Floor : Other : Steel covered with rubber

Bumper : Long Steel Extendable 20'

Fenders :

Mud flaps : Témisko
 Location : Back of gooseneck and at each axle

Land gear : Jost
 Crank : R/S

Lights : Truck-lite round type (2/s) 45° flasher
 LED lights
 Other: Beacon light at rear bumper
 Strobe lights in bumper on switch (clearance circuit)

Title hold :
 Location : Truck-lite

Tool box : Alum. Témisko FAB
 Dimensions : 25" X 24" X 48"
 Location : In front of tridem, on both sides

Flat Extendable **Drop**

Length : 53' to 218' with bumper

Width : 102"

Steering axles : 3

Suspension : Turner HT-250U

Scale-O-Matic COLAS Valve Shut-off valve

Axle Location :

Steering mecanism :
 Forced steer with front turn table
 Suspension and axles with turn tables

Steering control : Automatic Manual
 13 HP Honda power pack

Axles :
 D-22 for 17,5 wheels

Axle track : Other : 79

Brake type: Drum brakes

Seals : Stemco Guardian HP **Bearings :** Stemco

Brake Chambers: TSE 30/30T

Automatic Slack adjuster : Rockwell

Brake valve : Rockwell Wabco

A.B.S. Brake : 2S/1M
 Blue wire on first axle A.B.S. Plug N

Hubs : Dura Light 8 studs steel piloted hubs

Drums : Standard

Rims : Qty : 12
 17.5 x 6.75 Alum. machined finish

Plastic spacer (rim & rim) Plastic spacer (hub & rim)

Tires : Qty : 12
 Model: Michelin XTA2 ENERGY Size : 245/70R17.5

Tire carrier Témisko Fab :
 1 C/S

Hubodometer : None

Paint : Colour : Black Tape 100%

Trim : None
 Rim : Natural
Rack : None

- Special**
- Visual lock indicators for inter beam locking
 - Aluminum checkerplate on front coupler, Aluminum checkerplate front fenders
 - (4) supports for air and hydraulic lines/beam
 - Power pack in aluminum box on R/S
 - Double redundant hydraulic steering circuit.
 - On board steering control, Plug in remote control and wireless remote control (Lodar) + antenna
 - dual Hydraulic drop leg to facilitate extending
 - "D" rings on each side of the front and rear loading platforms
 - 180 ft of hydraulic lines from front to back
 - Oversized sign at rear

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.



TEMISKO



Blade Trailer

Extendible, Extendible, Extendible

With an impressive 180 feet of total length as our standard, it is ready to take on almost every blade on the market. The trailer was created with blade growth in mind. A 5th beam can be added in at anytime and still close up to 53 ft. The gooseneck swing clearance is high enough to accommodate a 4 axle truck.

The already best in class steering has been improved upon to now steer at 46 degrees. Thanks to the double redundant hydraulic steering, most corners are tackled with no help from the manual override.

Specifications

Width:	102
Length:	53' Closed, 180' Opened
Weight:	32,460 lbs
Steering angle:	46 degrees
Extendible bumper:	20'

5th beam option

Length:	53' Closed, 218' Opened
Weight:	36,230 lbs

