

HALE

TRAILER

BRAKE & WHEEL



A020871
VIN: A4520

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Xcalibur Extendable 48ft - 80ft Spring Slider Tridem (Check with your Fontaine Sales Rep for Pricing)
(Model: XCALIBUR XTP4880SS3)

	Est. Wt.: 18,396# +/- 3%
TRAILER - GENERAL	
Capacity: 80,000 lbs distributed - self-supporting, properly blocked	
Length: 48 feet (closed) to 80 feet (open)	
Width: 8 feet 6 inches	
DECK-FRONT	
Kingpin: 24 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Bulkheads: None	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
Front Corners: Tapered	
SUSPENSION	
Suspension: Sliding spring tandem	
Frame Rating: 80,000 lbs distributed - self-supporting, properly blocked	
Load Scale: None Standard	
DECK-MAIN	
Main Beams: Minimum grade 80 flanges	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inches centers	
Rubrail: 2 1/2 inch x 3/8 inch thick HD mill formed steel	
Conspicuity Tape: Per NHTSA specs - installed on rub rail	
Flooring: 1 1/8 inch wood	
Winch Track: Full-length steel on road side	
Sliding Winches: 12 - without straps	
Winch Straps: None	
Air and Electrical @ Extension Locks: Inside track system	
Tool Box: None	
DECK-REAR	
Bumper: Meets underride requirements	
Mudflaps: 1 set Fontaine	
AXLES	
Number of Axles: 3	
Axle Spindle: Tapered	
Axle Spread: 49 inches	
Brakes: Spring brakes, auto slacks	
Dust Shields: None	
SUSPENSION	
Suspension: Sliding spring tridem	
Suspension: Hutch H-9700 3 leaf spring slider - 60 inch adjustable	
Frame Rating: 80,000 lbs distributed - self-supporting, properly blocked	
ABS: 2S/1M - no cable or tool	
Load Scale: None Standard	
WHEELS AND TIRES	

Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white -	
Tires: 295/75R 22.5 14PR Economical OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: Sealed harness and LED Lights: 3 lights per side on rear with 4 inch flush mounted amber strobes (no battery back-up)	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.