

# HALE TRAILER BRAKE & WHEEL



**Resale Inventory**  
**A020873**  
**VIN: 128603**

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Jacksonville, FL:</b> 800-828-3055
<b>Baltimore, MD:</b> 888-601-7500	<b>Little Rock, AR:</b> 833-424-8944
<b>Boston, MA:</b> 800-854-5310	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Richmond, VA:</b> 866-839-3495
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

### TK110HDG Commercial Hydraulic Detachable 110,000 Lbs in 12 feet

#### STANDARD EQUIPMENT

Hydraulic self-lifting detachable gooseneck  
(can lift above or below transport positions)  
Gooseneck doesn't require ground bearing pads

Rubber mounted sealed lights and harness system  
Electrical system per DOT regulations  
Red & white conspicuity markings  
Blasted prior to paint

#### 12005-110HDG Com-Base Trailer

1	12005	Open Deck	TK110HDG Commercial Hydraulic Detachable 110,000 Lbs in 12 feet
1	12011	Gooseneck	12' 10" (110" and 86" swing) hydraulic detachable gooseneck
1	12014	Gooseneck	PTO Hydraulics
1	14692	Gooseneck	5-position gooseneck height adjustment +/- 3"
1	14693	Gooseneck	Hydraulic gooseneck support arm
1	14694	Gooseneck	Air-activated, positive self-locking pin
1	14695	Fifth Wheel / King Pin	50" loaded fifth wheel height

1	09998	Deck Length	Alternative Option Selected. See Add'l Options Section Below.
1	12040	Deck Width	108" deck width deck and wheel area
1	12041	Deck Width	Full-width deck
1	09998	Main Deck	Alternative Option Selected. See Add'l Options Section Below.
1	14697	Main Deck	I-beam crossmembers on 24" centers
1	14698	Main Deck	4" stubs between crossmembers in outer bays for 12" centers in outer bays
1	14699	Main Deck	Triangle cut-outs on deck beams and bolster
1	14700	Main Deck	Knuckle trough at rear of deck - 72" long, covered with 1/4" steel
1	12033	Main Deck	Top flange reinforcement
1	12050	Wheel Area	Fixed wheel area
1	12052	Wheel Area	No wheel covers
1	14701	Wheel Area	Lowered crossmembers in wheel area
1	14702	Wheel Area	Full depth boom trough in wheel area
1	14703	Wheel Area	10ga. Steel boom plates bolted in boom trough
1	09998	Wheel Area	Alternative Option Selected. See Add'l Options Section Below.
	12059	Wheel Area	Add upper brackets for hydraulic booster
1	14707	Decking	1 3/4" Apitong decking (raised)

1	15842	Tie Downs	Additional d-rings to fill out deck, 2 D-rings on wheel area
1	12031	Tie Downs	2 pr d-rings in knuckle trough
1	14262	Tie Downs	2 pr d-rings in wheel area transition
1	14263	Tie Downs	1 pr d-rings located above each crossmember in wheel area
1	14224	Tie Downs	1 pr d-rings on rear flange of gooseneck riser section
4	17495	Tie Downs	Bent D-rings - per pair

*inside main beam on top of bottom flange spaced evenly starting behind storage bay and stopping before knuckle trough*

1	15843	Outriggers / Side Extensions	Swingout outriggers, with pullout HD outrigger at front, double swingouts at center, and 4' storage pan
1	15851	Outriggers / Side Extensions	Outrigger Planks Loose
1	14712	Ramps	Front ramps (31" std deck, 42" tapered deck, N/A on rail deck)
3	12060	Suspensions / Axles	25,000-lb. (5/8" wall) axles
1	14713	Suspensions / Axles	Air ride suspension
1	14715	Suspensions / Axles	Air suspension control panel located in end of bolster ahead of rear axle (includes adjustable ride height cable if applicable)
1	14718	Suspensions / Axles	One-piece oil seals
1	15831	Suspensions / Axles	Raising/lowering air control panel (includes liquid filled air gauge)

1	09998	Suspensions / Axles	Alternative Option Selected. See Add'l Options Section Below.
1	15850	Suspensions / Axles	3rd axle air lift with dual ride height control
1	12070	Axle Spacing	55" axle spacing (single axle booster reinforcement)
1	12078	Brakes	No ABS with Spring brakes (1st and 2nd axles)
1	14719	Brakes	16.5" x 7" air brakes
1	14720	Brakes	Automatic slack adjusters
3	08214	Hub / Drum	Steel hub-piloted - Cast drum - tapered spindle (per complete axle)
6	12849	Wheels (inside)	8.25 x 22.5 10-hole steel disc wheel
6	12849	Wheels (outside)	8.25 x 22.5 10-hole steel disc wheel
1	10058	Spare Wheel	No Spare Wheel
12	16221	Tires	Continental 275/70R22.5 HSR2 - 18 ply (tire only) (per tire) ILO Std General 255/70R22.5 HT - 16 Ply
1	10059	Spare Tires	No spare tire
1	12084	Lights / Electrical	One pair of 4" round quad flash amber strobes at rear w/ switch mounted on drivers side rear bolster ILO 3rd tail light package
1	14722	Lights / Electrical	LED Lights

**Order Build Sheet**

<b>1</b>	<b>14724</b>	<b>Lights / Electrical</b>	<b>7-pole electrical connector at front</b>
<b>1</b>	<b>12087</b>	<b>Lights / Electrical</b>	<b>Remote flasher w/ battery back-up with switch mounted on drivers side rear bolster</b>
<b>1</b>	<b>14727</b>	<b>Flagholders</b>	<b>Flagholders, front of deck and rear of trailer</b>
<b>1</b>	<b>14728</b>	<b>Flagholders</b>	<b>Wide load sign brackets only</b>
<b>1</b>	<b>08009</b>	<b>Paint</b>	<b>Epoxy primer</b>
<b>1</b>	<b>08024</b>	<b>Paint</b>	<b>S7203 Black with white decals</b>
<b>1</b>	<b>14721</b>	<b>Flaps, Mud Guards &amp; Fenders</b>	<b>Mudflaps</b>
<b>1</b>	<b>60015</b>	<b>Main Deck - Special</b>	<b>60015 TK110HDG - 18" loaded deck height with 6" ground clearance ilo std 24" loaded deck height with 8" ground clearance.</b>
<b>1</b>	<b>60013</b>	<b>Deck Length - Special</b>	<b>60013 110HDG, 29' Deck length</b>
<b>1</b>	<b>61317</b>	<b>Tie Downs - Special</b>	<b>61317, TK110HDG, 12 pair keyslots evenly spaced on inside of outside beam on main deck, 6" outer flanges</b>

**Requested changes:**

Add: 14638 Brackets, air and electrical for additional axles

**Requested changes:**

Change OAL to 56'-1" ilo 56'-0"

No Change to VIN

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.