

Model Year - 2024LIV

LineModelDescriptionNotesQty1440B-50CA440B-50CA - 50' Traveling Axle1



Description Qty

Trailer Model - 440B-50CA 1

Standard Equipment

Capacity - 80,000 Lbs.

Deck Rating - 50,000 Lbs. in 10'

Axles - 2-25,000 Lb. Dual Tire, Oil Bath Bearings; Prepped for Tire Inflation

Suspension - Neway RLU228 Air Ride 22,500 Lb. Capacity

Pin Setting - 21"

Loaded Ground Clearance - 14" at Bottom of Gooseneck

Loaded Deck Height - 37"

Lights - Grote MicroNova® LED Clear Lens; Enhanced Stop, Turn, Tail and Tail; Rear Amber Strobe (10 Year Warranty)

Tie Downs - Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers

Load Angle - 6.5 Degree

Base Options

Toolboxes - Side Opening Toolboxes 1
Deck Width - 8' 6" Wide Deck (Standard) 1
Deck Extensions - 27" Aluminum Pull-Outs 1
Trailer Length - 50'
Swing Clearance - 83.5"

1

Parking Stands

Parking Stands - Jost 2 Speed (Standard)

Winch and Accessories	
Winch - 20K Braden, Planetary, 2 Speed with Air Release/Spring Tension	1
Cable Roller Guide	1
Upper Deck Slope Wear Protection - Wear Plate (Standard)	1
Wireless Remote Control (6 Function: Tilt, Travel, and Winch)	1
Deck and Accessories	
Slope Mounted Dual LED Work Lights	1
Folding Step(s) - Street Side (Galvanized)	1
Deck Type - 1-3/8" Apitong Wood Decking	1
Hydraulic Power Source	
Kohler EFI, 25 HP, Gas Powered Hydraulic Engine Package with Cover - Front Extension Mounted	1
Tires and Wheels	
Tires - 235/75R 17.5 Double Coin (Standard)	1
Outside Wheel Type - 17.5 Polished Aluminum Wheel (8 Bolt)	1
Inside Wheel Type - 17.5 Steel Hub Wheel (8 Bolt) (Standard)	1
Tire Air System - PSI Air Inflation System	1
Paint and Special Options	
Standard Landoll Branded Decals (Affects Lower Deck Only)	1
Hot Dip Galvanizing	1
Hot Dip Galvanized Under Carriage Weldment	1
Hot Dip Galvanized Bumper	1
Paint over Galvanizing (Side Frame Web Only)	1
Wet Paint Color - Red	1