| | | SALES | RENTALS | PARTS | SERVICE |
|-------------------------|------------------|--|--------------|-------------------|--------------|
| | | Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| | | Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| TRAILER | | Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| BRAKE | & WHEEL | Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| | | Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| FONTAINE" HEAVY-HAUL | Resale Inventory | Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| | A021106 | Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| | VIN: 5A1545 | HaleTrailer.com @haletrailer f 🎔 🖆 🐵 🎬 | | | |

You 800-232-6535 *FINANCING AVAILABLE

| RENEGADE XN20 (Model: RENLXT40NF*829542) | | | | | |
|---|--|--|--|--|--|
| Detailed Specifications General | | | | | |
| SKU | RENLXT40NF*829542 | | | | |
| Capacity | 40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads | | | | |
| Length (Trailer Only) | 50 feet 1 inch (closed); 71 feet 1 inch (open) | | | | |
| Width | 8 feet 6 inches | | | | |
| Compatibility | Designed to Accept Optional Third Flip Axle | | | | |
| Accent Package | Stainless Steel Bumper Insert | | | | |
| Weight | Est. Configured Weight: 22350# +/- 3% | | | | |
| Gooseneck | | | | | |
| Gooseneck Design | Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11 feet 11 inches overall Gooseneck Length) Set Up for Wetline Operation | | | | |
| Loaded Fifth Wheel Height | 50-inch Nominal Loaded Fifth Wheel Height with 5 Ride Height Positions | | | | |
| Power Source | Set Up for Wet Line Operation | | | | |
| VIN Plate | Bilingual VIN Plate | | | | |
| Registration/Document Holder | Install Registration/Document Holder | | | | |
| Deck | | | | | |
| Framework | All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs | | | | |
| Deck Design | Flat Level Deck Design | | | | |
| Deck Length | 29 feet 0 inches Clear Deck Length (closed) - 50 feet 0 inches (open) | | | | |
| Loaded Deck Height | 20 inches with 6 inches Ground Clearance | | | | |
| Crossmembers | On 24 inch Centers | | | | |
| Deck Lock | First 5 Spaced Approx. 12 inches; Others Every 50 inches | | | | |
| Flooring | 1 3/8 inch Nominal Wood (Full Width) | | | | |
| Recessed Floor Mounted D-Ring Package | None | | | | |
| Front Ramps | None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats | | | | |
| Extension Brackets | Outriggers - 14 Pair - 28 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type | | | | |
| | Rear Bridge: General | | | | |
| Front Bogie Ramp | Sloped Steel Bogie Ramp (Full Width) | | | | |
| Mini Boom Trough and Traction Cleats | None | | | | |
| Deck to Bogie Connection | Fixed | | | | |
| Covered Rear Bogie | Rear Bogie Platform with 1 1/8 inch Wood Floor | | | | |
| Rear Bogie Height | 41 inches | | | | |
| Connections for Future Axle Attachment | Air and Electrical Connections to Go Along with Connecting Ears | | | | |
| Rear Bridge: Axles | | | | | |
| Number of Axles | 2 | | | | |
| Axle Capacity | 25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components | | | | |
| Axle Spread | 54.5 inches (Between Axles) | | | | |
| Spring Brakes | Spring Brakes (2 Axles) | | | | |
| Dust Shield | None | | | | |
| Hubodometer | None | | | | |
| Rear Bridge: Suspension | | | | | |
| Suspension | Air Ride with Automatic Controls | | | | |
| ABS | 4S/2M System without Diagnostic Tool and Cable | | | | |
| Ride Height Control | Automatic/Manual Raise/Lower Control | | | | |
| Liquid Filled Gauge | Included | | | | |
| Load Scale | None | | | | |
| h | + | | | | |



Detailed Specifications

| Wheels and Tires | | | | | |
|--|---|--|--|--|--|
| Wheels | 8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted | | | | |
| Tires | 255/70R 22.5 H Ply OEM Standard | | | | |
| Inflation | None | | | | |
| Lighting | | | | | |
| Electrical System | DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes | | | | |
| Tail Lights | 3 Tail Light Package | | | | |
| Marker Lights | 8 Marker Lights Per Side Including Mid-Turn | | | | |
| Special | Not Available on This Model | | | | |
| Electrical Receptacle | J560 7-Pin Connector | | | | |
| Paint | | | | | |
| Paint | Fontaine Black Polyurethane Enamel | | | | |
| Miscellaneous | | | | | |
| Lash Rings | 12 Pair - 24 Total | | | | |
| Flag Holders | 2 Pair Flag Holders | | | | |
| | Additional Options | | | | |
| Flip Axle | None | | | | |
| Dust Shields on Flip Axle | None | | | | |
| Terms | | | | | |
| Please Note | Price Includes Commodity Surcharges | | | | |
| Commercial Terms | Ex Works- Springville, AL, USA | | | | |
| | RENEGADE XN20 | | | | |
| | | | | | |
| RENEGADE XN20 Base Model (Note: Options not shown) | | | | | |



