

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A021191
VIN: 538315

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Infinity Flat 48' Wide Spread Air (Model: HAICF12WSA)

Quantity:

Length / Width: 48 feet x 102 inches

Suspension Type: Wide spread air

Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch aluminum with 4 Apitong wood nailer strips

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive Revolutionary RASR Rail Technology – one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: 15 pair recessed in siderails

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets & Bulkhead: None standard

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 295/75R 22.5 14PR OEM standard tires- STANDARD

Tire Inflation System: None standard

Suspension Detail: Hendrickson AANT23K Intraax air ride

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None standard

Front Corners: Tapered steel

Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets underride requirements - painted steel

Mudflaps: 2 sets **Customer Furnished; Spring** loaded brackets behind front axle

Spare Tire Carrier: None standard

Winch Track: Full length integrated double L type aluminum on both sides - STANDARD

Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD

27' Winch Straps: None standard

30' Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: **Install registration holder - OEM standard**

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.