



KALYN SIEBERT A021306
VIN: 174556

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer 

800-232-6535 *FINANCING AVAILABLE

Trailer Model: Kalyn Hydraulic Sliding Axle KS-HSA-3A-55T-53

KS-HSA-3A-55T-53 Standard Equipment	
Net Capacity:	55 Tons 110,000 lbs Distributed in 53 ft, 70,000 lbs Concentrated in 10 ft
Nominal:	53 feet OAL 8 feet 6 inches Wide
GOOSENECK:	<p>10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')</p> <p>48" Loaded 5th Wheel Height, 18" Kingpin Setting</p> <p>86" Swing Radius (48' & 50') / 96" Swing Radius (53')</p> <p>20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable</p> <p>Work lights on the winch 2 Tool compartments</p> <p>Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings</p> <p>Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door</p> <p>2-Speed Landing Gear , Crank Handle Roadside</p>
DECK:	<p>Nominal Deck Length: 41.5 feet</p> <p>Nominal Deck Width: 102 in</p> <p>Loaded Deck Height: 37 in</p> <p>4 Beam design - 100,000 psi yield flanges & 80,000 web minimum</p> <p>14" tall main beams and 15" tall side rails</p> <p>4" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck (full width)</p> <p>Double Key Hole Chain Slots in Upper Flange on 36" Centers</p> <p>Double Key Hole Chain Slots Along Center of Deck on 36" Centers</p> <p>Reinforced Rear Approach Plate with 6 Chain Slots</p> <p>Cable Roller Centered at Front of Lower Deck</p>
	<p>Dump angle 16° Loading angle 7°</p> <p>SUSPENSION:</p> <p>25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles</p> <p>50" axle spacing 71" track</p> <p>12-1/4" x 7-1/2" Brakes ABS Module: 4S2M</p> <p>Auto Slack Adjusters and Spring Brakes on all Axles</p> <p>6.75 x 17.5 Hub Piloted Disc Wheels</p> <p>235/75 R 17.5 16PR Tires Manual Dump Valve</p> <p>Suspension: Ridewell or Equivalent Air ride Air Ride</p> <p>Alignment Bracket for Sliding Suspension</p> <p>GENERAL:</p> <p>12 Volt System with 7 way Sealed Harness</p> <p>DOT Rubber Mounted Sealed Beam LED Lights</p> <p>Epoxy Primer & Black Polyurethane Paint</p> <p>2 Function Wireless Remote for Winch</p> <p>Heavy Duty DOT Approved Bumper</p> <p>Red & White Conspicuity tape KS Mud Flaps</p> <p>3 LED marker lights each side including mid turn</p> <p>Strobe light with toggle switch on rear</p>

Kalyn Hydraulic Sliding Axle Optional Equipment	
Models	<input checked="" type="checkbox"/> 3 Axle, 55 Ton, 53' Model
Options	<input checked="" type="checkbox"/> Bolt on Side Step (Driver Side) <input checked="" type="checkbox"/> Aluminum Wheels Outside all Axles <input checked="" type="checkbox"/> OEM 235/75 R 17.5 16PR Tires <input checked="" type="checkbox"/> AirWeigh Load Scale <input checked="" type="checkbox"/> Tire Inflation <input checked="" type="checkbox"/> Central Lube - 24 Point Manual <input checked="" type="checkbox"/> 30,000 Lbs Winch <input checked="" type="checkbox"/> Prepped & plumbed for future bolt-on dock leveler installation

Estimated Weight of the Equipment with the options : **22,476 lbs.**