

HALE TRAILER

BRAKE & WHEEL

1050-F PNEUMATIC DRY BULK



Resale Inventory

A021340

VIN: 034035

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

VESSEL			
GVWR	72 GVWR	WEIGHT	8919 +/- 3%
MODEL	1050-F	MODEL NO.	TN1050APB
COMMODITY	SAND		
VESSEL CONSTRUCTION	SMOOTH EXTERIOR - INTERNAL RINGS		
LENGTH	42 FT.		
OPERATING TEMP	185 DEG - (MAX)		
OPERATING PRESSURE	14.7 P.S.I. (HYDRO TESTED TO 22.5 P.S.I.)		
VESSEL THICKNESS	.190 ALUMINUM 5454-H32 (STANDARD)		
VESSEL FINISH	MILL FINISH - VESSEL (STANDARD)		
COMPARTMENTS	SINGLE COMPARTMENT (STANDARD)		
LOWER CONES	WELD ON - 45 DEG (STANDARD)		
# OF MANHOLES	3 - (STANDARD)		
MANHOLE LOCATION	OVER EACH HOPPER (STANDARD)		
MANHOLE STYLE	BETTS MODEL 8555 20 IN. MANWAY (STANDARD)		
PIPING / FITTINGS			
UNLOAD TYPE	PRESSURIZED		
AIR INLET LINE			
AIR INLET SIZE	3 INCH - INLET, MANIFOLD, VALVE	HOSE HANGER INCLUDED WITH COUPLER	
CHECK VALVES	2-CHECK VALVES (1 @ AIR INLET)-(1UP STREAM OF FRONT HOPPER DISCHARGE)		
AIR INLET LOCATION	STREET SIDE FRONT		
AERATION			
AERATORS	3 PER HOPPER (STANDARD)		
AERATION TYPE	B.T.I. SPIN FLOW AERATION KIT @ EACH HOPPER W/ WEAR PLATES		
AERATION LINE LOCATION	STREET SIDE		
AERATION CONTROL	3" BTI MAXXLIFE BUTTERFLY VALVE (2" B'FLY VALVE AT EACH HOPPER)		
	REGULATES AIR FLOW TO AIR MANIFOLD LINE. 2 INCH - HOSES SUPPLYING AIR TO AERATION SYSTEM.		
SEAT	BLACK RUBBER SEAT		
DISK	IRON DISK		
HANDLE TYPE	ALUMINUM		
HANDLE POSITION PLATE	MANUAL 10-POSITION		
PROP / PRES CONTROL VALVE			
HOUSING	3" BTI MAXXLIFE BUTTERFLY VALVE		
SEAT	BLACK RUBBER SEAT		
DISK	IRON DISK		
HANDLE TYPE	ALUMINUM		
HANDLE POSITION PLATE	MANUAL 10-POSITION		
BLOW DOWN LINE			
HOUSING	3" BTI MAXXLIFE BUTTERFLY VALVE		
SEAT	BLACK RUBBER SEAT		
DISK	IRON DISK		
HANDLE TYPE	ALUMINUM		
HANDLE POSITION PLATE	MANUAL 10-POSITION		
RELIEF PRESSURE	15 P.S.I.		
BLOW DOWN LOCATION	STREET SIDE FRONT		
TOP AIR			
TOP AIR	3" BTI MAXXLIFE BUTTERFLY VALVE		
TOP LINE LOCATION	STREET SIDE FRONT		
PRODUCT VALVE			
PRODUCT VALVE SIZE	5" BTI MAXXLIFE BUTTERFLY VALVES		
HOUSING	ALUMINUM BODY		
SEAT	BLACK RUBBER SEAT		
DISK	IRON DISK		
HANDLE TYPE	EXTENDED ALUMINUM HANDLE		
HANDLE POSITION PLATE	MANUAL 5-POSITION		
PRODUCT TEE			
PRODUCT TEE TYPE	5 X 4 BTI SANDHOG BOTTOM DROP TEE'S		
PRODUCT LINE			
LINE CONNECTIONS	4 INCH SCHD. 40 GALVANIZED STEEL GROOVE TO GROOVE CLAMPS @ FRONT AND REAR RUBBER SLEEVES WITH WORM GEAR CLAMPS		
REAR DISCHARGE DISCHARGE LOCATION	4 INCH SCHD. 40 GALVANIZED STEEL EXTEND THROUGH AXLES TO REAR		
GAUGE ENCLOSURE	1		
GAUGES	1 - LINE P.S.I. / 1 - TANK P.S.I. - (INSIDE ILLUMINATED ENCLOSURE)		
GAUGE LOCATION	STREET SIDE - REAR - FORWARD OF TANDEM (STANDARD)		

ACCESSORIES		
LADDER	LADDER AT REAR - DOUBLE HAND RAIL (STANDARD)	
WALKWAY	ADHESIVE BACKED SKID RESISTANT TAPE BETWEEN TOERAILS (STANDARD)	
HAND RAIL	NONE	
TOE RAIL	FULL LENGTH - BOTH SIDES (STANDARD)	
HOSE TUBE	1 - 8 x 21' ALUMINUM HOSE TUBE (STANDARD) - (CURB SIDE)	
HOSE TROUGH	NONE	
TIRE CARRIER	NONE	
FENDERS	ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR (STANDARD)	
MUD FLAPS	ANTI-SAIL FLAPS - REAR OF FRONT FENDERS AND REAR OF BACK FENDERS (STANDARD)	
TOW HOOK	IN FRAME - BETWEEN RAILS	
CHASSIS		
MODEL TYPE	TANDEM	
5TH WHEEL LOCATION	GALVANIZED, ADJUSTABLE	
5TH WHEEL HEIGHT	48 IN.	
LANDING GEAR	JOST - 5 YEAR NO LUBE - D.S. (STANDARD)	
SUSPENSION	HEND. INTRAAX AAT230 W/250 BAGS RAISED AXLE TP SPINDLE	
AXLES	71.5 RAISED CENTER AXLES	
WHEEL END PACKAGE	NONE	
SUSPENSION CONTROLS	AUTOMATIC DUMP ON EMERGENCY GLADHAND (STANDARD)	
SCALE SYSTEM	LOAD GAUGE - STREET SIDE REAR (STANDARD)	
HUBS & DRUMS	CENT W/ALUM. HUB. HP OB 10 STUD TP, LS, 7 INCH (STANDARD)	DOCUMENT HOLDER INCLUDED
TIRE & RIM SIZE	22.5 INCH - TIRES & RIMS (STANDARD)	
TIRE TYPE	8 - BF GOODRICH ST230 11R 22.5 16 PLY (STANDARD)	GENERAL S360 11R 22.5
RIM TYPE	ALCOA 8.25 X 22.5 ALUMINUM WHEELS BUFFED	
TIRE INFLATION SYSTEM	NONE	
A.B.S.	(1) 4S2M MERITOR / WABCO (STANDARD)	
BRAKE SHOES	7" XL, W/30-30 CHAMBERS (STANDARD)	
SLACKS	STANDARD	
HUBODOMETER	NONE	
SYNTHETIC LUBRICATION	NONE	
LIGHTS		
REAR I.D. LIGHTS	(I.D.) (I.D.) (I.D.)	
"HIGH MOUNT" BRAKE LIGHT	DUAL FUNCTION REAR I.D. LIGHTS BRIGHTEN WHEN BRAKES ARE APPLIED	
REAR LIGHT PANEL	(TURN) (STOP) (STOP) - (STOP) (STOP) (TURN)	
LIGHT TYPE	GROTE LED W/GROMMETS (STANDARD)	
MARKER LIGHTS	2 EACH SIDE - FRONT AND REAR (STANDARD)	
MIDTURNS	2-PAIR COMBO MIDTURNS (STANDARD)	
BACK-UP LIGHTS	NONE	
WORK LIGHTS	NONE	
AUXILARY CABLE (4 OR 7 WAY)	NONE	
PAINT		
SUSPENSION COATING	GALVANIZED HANGERS WITH HENDRICKSON BLACK SOFT COAT	
PAINT COLOR	MAC BLACK (STANDARD)	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.