

**Model:** Axle Attachment **Capacity in tons:** 55

## 1. DESIGN PARAMETERS

Mudflaps

Type Flip-up & removable

Framework Fabricated

Suspension 30,000# Capacity Ridewell air

Axle attachment connections Attachment to be equipped with top and bottom connecting ears, pin tubes with

bolts and nuts, shims, chrome tapered connecting pins, air and electrical

connections

Axle capacity 25,000# - GAWR 24,700# Brakes 16-1/2" x 7" air actuated

Wheels Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil

seals, inner wheels steel with outer aluminum wheels polished

Anti-lock brake system None

Tires Four (4) 275/70R22.5 (H) 16PR radials

Bridge width 8'-6"

Axle frame height 41" frame; 37" bolster Half bolster With flag holder slots Lash rings 2 at rear bent style

Lights and wiring 12 volt system with the following:

All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style

4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired

to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up

Paint Valspar standard Talbert red, R-Cure 800 series paint with ZINC RICH primer

Talbert anti-sail

Additional design specifications 1) 2 rubber bumpers on top

2) 54" axle spacing3) Over ride chains

4) Estimated and 20

4) Estimated empty weight: 2,850#

Compatibility With existing Talbert Trailer, SN43771, 60SA-RC