

HALE

TRAILER

BRAKE & WHEEL



A021490
VIN: 5A4634

SALES | RENTALS | PARTS | SERVICE

| | |
|-------------------------------------|---------------------------------------|
| Allentown, PA: 800-383-8894 | Jacksonville, FL: 800-828-3055 |
| Baltimore, MD: 888-601-7500 | Little Rock, AR: 833-424-8944 |
| Boston, MA: 800-854-5310 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Richmond, VA: 866-839-3495 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

| Workhorse 55 PVR PRO (Model: WORKHORSE 55 PVR PRO) | |
|---|--------------------------|
| | Est. Wt.: 23,590# +/- 3% |
| TRAILER - GENERAL | |
| Capacity: 50 tons in 12-foot length or 55 tons in 16-foot with 4 axles close coupled - GAWR and tire ratings determine legal payloads | |
| Length (Trailer Only): 53 feet 0 inches | |
| Width: 8 feet 6 inches | |
| Compatibility: Designed to Accept Optional 51/60 Rear Axle | |
| GOOSENECK | |
| Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 108 inches (12ft 2in overall gooseneck length) set up for wetline operation | |
| Loaded Fifth Wheel Height: 52 in nominal loaded fifth wheel height with 7 ride height positions | |
| Kingpin: Removable kingpin at 82 and 108 inch radius | |
| Power Source: Set Up for Wet Line Operation | |
| Tool Box: None | |
| Hydraulic Fittings: OEM Standard 1/2 inch | |
| DECK | |
| Framework: All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs | |
| Deck Design: Flat level deck design (tapered beam design) | |
| Deck Length: 24 feet 0 inches Clear Deck Length | |
| Loaded Deck Height: 22 inches with 6 inches Ground Clearance | |
| Crossmembers: High Density Crossmember Package- Additional stub crossmembers, net spacing of 11 inches | |
| Flooring: 1.5 inch nominal apitong wood (full width) | |
| Front Ramps: Apitong Wood Filled Double Hinged Adjustable Width to 44 inches inside to inside (9 degree load angle) | |
| Center Roller Ramp: None | |
| Extension Brackets: 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type | |
| Tool Box: 1 fully covered toolbox with lockable lid (front of deck) (When 2-piece center insert is removed, perforated plate under hammer plate becomes additional storage area- rear of deck (Storage area not accessible when standard covered rear bogie is in place) | |
| Hammer Plate: Hammer Plate installed over recessed crossmembers. Perforated plate under hammer plate forming one storage area; includes 1 pair of D rings (Hammer Plate will not be accessible with the standard removable covered rear bogie) | |
| REAR BRIDGE | |
| Front Bogie Ramp: Sloped (17 degree angle) | |
| Boom Trough: Low Boom Well, with V crossmember with bolt-in V pan | |
| Deck to Bogie Connection: Fixed w/ ramps outboard mainbeams, apitong wood filled | |
| Bolsters: Recessed | |
| Covered Rear Bogie: Load Bearing Wheel Covers- Apitong Wood Filled with 2-piece center insert for full width loading | |
| Rear Bogie Height: 45 1/4 inches | |
| Connections for Future Axle Attachment: Air and Electrical Connections to Go Along with Connecting Ears | |

| | |
|--|--|
| Accent Package: None | |
| AXLES | |
| Number of Axles: 3 | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 50 inches (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount | |
| Spring Brakes: Spring brakes on axle 2 | |
| Dust Shields: None | |
| Hubodometer: None | |
| SUSPENSION | |
| Suspension: Air Ride | |
| ABS: None | |
| Third Lift Axle: Air Lift Installed on Third Axle | |
| Chain Lift: First Axle (acts as a limit chain) | |
| Override Chains: Override Chains Axle 2 & 3 | |
| Ride Height Control: 7-position mechanical ride height control system | |
| Dump Valve: Automatic/Manual Raise/Lower Control | |
| Liquid Filled Gauge: None | |
| Load Scale: None Standard | |
| WHEELS AND TIRES | |
| Wheels: 8.25 x 22.5 LVL One Buffed Outside/Steel Inside - Hub-Piloted | |
| Tires: 275/70R 22.5 H Ply OEM Standard | |
| Tire Inflation System: None | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| LIGHTING | |
| Electrical System: DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes | |
| Tail Lights: 3 Tail Light Package | |
| Marker Lights: 3 Marker Lights Per Side Including Mid-Turn | |
| Electrical Receptacle: J560 7-Pin Connector | |
| Additional Marker Lights: None Standard | |
| PAINT | |
| Paint: Fontaine Black Polyurethane Enamel | |
| MISCELLANEOUS | |
| Lash Rings: 17 Pair - 34 Total | |
| Flag Holders: 2 Pair Flag Holders | |
| VIN Plate: Bilingual VIN Plate | |
| Registration/Document Holder: Registration/document holder installed | |
| Flip Axle: None | |
| Dust Shields on Flip Axle: None | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.