



A021605
VIN: 174555

SALES | RENTALS | PARTS | SERVICE

- | | | | |
|-----------------|--------------|-------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Kalyn Hydraulic Sliding Axle KS-HSA-3A-55T-53

KS-HSA-3A-55T-53 Standard Equipment

Net Capacity: 55 Tons 110,000 lbs Distributed in 53 ft, 70,000 lbs Concentrated in 10 ft
 Nominal: 53 feet OAL
 8 feet 6 inches Wide

GOOSENECK:

- 10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')
- 48" Loaded 5th Wheel Height, 18" Kingpin Setting
- 86" Swing Radius (48' & 50') / 96" Swing Radius (53')
- 20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable
- Work lights on the winch 2 Tool compartments
- Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings
- Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door
- 2-Speed Landing Gear, Crank Handle Roadside

DECK:

- Nominal Deck Length: 41.5 feet
- Nominal Deck Width: 102 in
- Loaded Deck Height: 37 in
- 4 Beam design - 100,000 psi yield flanges & 80,000 web minimum
- 14" tall main beams and 15" tall side rails
- 4" I-beam cross members on 9" Centers, 1-3/8" Apatong Deck (full width)
- Double Key Hole Chain Slots in Upper Flange on 36" Centers
- Double Key Hole Chain Slots Along Center of Deck on 36" Centers
- Reinforced Rear Approach Plate with 6 Chain Slots
- Cable Roller Centered at Front of Lower Deck

SUSPENSION:

- 25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles
- 50" axle spacing 71" track
- 12-1/4" x 7-1/2" Brakes ABS Module: 4S2M
- Auto Slack Adjusters and Spring Brakes on all Axles
- 6.75 x 17.5 Hub Piloted Disc Wheels
- 235/75 R 17.5 16PR Tires Manual Dump Valve
- Suspension: Ridewell or Equivalent Air ride Air Ride
- Alignment Bracket for Sliding Suspension

GENERAL:

- 12 Volt System with 7 way Sealed Harness
- DOT Rubber Mounted Sealed Beam LED Lights
- Epoxy Primer & Black Polyurethane Paint
- 2 Function Wireless Remote for Winch
- Heavy Duty DOT Approved Bumper
- Red & White Conspicuity tape KS Mud Flaps
- 3 LED marker lights each side including mid turn
- Strobe light with toggle switch on rear

Models

Kalyn Hydraulic Sliding Axle Optional Equipment

3 Axle, 55 Ton, 53' Model

Options

6 Function Wireless Remote

Bolt on Side Step (Driver Side)

Aluminum Wheels Outside all Axles

OEM 235/75 R 17.5 16PR Tires

AirWeigh Load Scale

Tire Inflation

74,000 lb Dock Levelers (Simultaneous Controls)

Central Lube - 24 Point Manual

30,000 Lbs Winch

Estimated Weight of the Equipment with the options : **22,726 lbs.**

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.