

HALE TRAILER BRAKE & WHEEL



Resale Inventory
A021607
VIN: 572819

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

MECHANICAL DETACHABLE DOUBLE DROP EXTENDABLE LOWBOY

MODEL: RENEGADELXT40 (Renegade LXT40 Air Tandem)

Capacity:	40 Tons in 16' length – GAWR and tire ratings determine legal loads
Load Base:	16' rigid 2-point load centered in deck
Framework:	All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs
Compatibility:	Designed to accept optional flip neck extension and 3 rd flip axle
Length/width:	47'11" –See deck length options-102" wide
Gooseneck Design:	Mechanical removable with removable fifth wheel guide rollers-Combination figure -8 plate – which provides 50" and 52" loaded-Swing radius of 81"
Gooseneck Platform:	Full width gooseneck platform with 1 1/8" wood floor
Flip Box:	None
Tool Box:	None
Gooseneck Fenders:	Aluminum fenders at rear of gooseneck
Electrical Receptacle:	J560 7-pin connector
Deck Design:	Flat level telescopic deck design
Deck Length:	34' clear deck length (retracted) – 60' (extended) Overall Length is 53'
Loaded Deck Height:	20" with 6" ground clearance
Flooring:	1 3/8" nominal wood (full width)
Recessed Floor Mounted	
D-Ring Package:	None
Crossmembers:	On 24" centers
Front Ramps:	None, front of deck sloped top down to assist in loading with traction cleats
Extension Brackets:	Mounting brackets only
Front Bogie Ramp:	Sloped steel bogie ramp (full width)
Mini Boom Trough & traction Cleats:	None
Deck to Bogie Connection:	Fixed
Number of Axles:	2
Axle Capacity:	25,000# nominal capacity per axle Note: GAWR determined by suspension type, brakes, tires and other components
Axle Spread:	54.5" spread (between axles)
Brakes:	16.5" x 7" with 5.5" auto slacks – heavy duty brake drums – outboard mount
Spring Brakes:	Spring brakes on 2 axles
Dust Shields:	None
Spring Brakes:	Spring brakes on 2 axles
Suspension:	Air ride with automatic controls
Tires:	255/70R 22.5 H ply OEM standard
Wheels:	8.25 x 22. 5 steel disc - hub piloted
Covered Rear Bogie:	Rear bogie platform with 1 1/8" wood floor
Rear Bogie Height:	41"
Bumper:	3 tail light package
Connections for Future Axle Attachment:	Air and electrical connections to go along with connection ears

Width:	8' 6"
Electrical System:	DOT sealed beam and harness with LED lights
Flip Axle:	None
Dust shields on flip axle:	None
Flip Axle Strobe Light Kit:	None
Paint:	Fontaine BLACK polyurethane enamel
Lash Rings:	9 Pair – 18 Total
Flag Holders:	3 pair flag holders
ABS:	4S/2M system without diagnostic tool and cable
Liquid Filled Gauge:	Included
Marker Lights:	8 Marker lights per side including mid-turn
Accent Package:	Stainless steel accent package
VIN Plate:	Bilingual VIN plate
Registration/Document Holder:	Installed
Estimated Weight:	21,315# +/-3%

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.