

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A021774
VIN: 033019

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Model: 5053TA
Capacity in tons: 50

1. GOOSENECK

Gooseneck design	LP Fixed
Upper deck length	11'-6"
Loaded 5th wheel height	48"
Swing radius	96" with 18" kingpin setting
Planetary winch	20,000# hydraulic with air clutch; 105' of 5/8" diameter cable with shackle
Power source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Electrical receptacle	Seven pin connector
Tool Box	Integrated in neck with 2 chrome hinges and 1 chrome latch per side on tool box and valve control box
Landing gear	2 speed Jost with crank on driver's side
Auxiliary Air Reservoir	Yes
Spare tire carrier	None
Additional gooseneck specifications	None

2. DECK

Deck section design	Four beam
Deck section length	41'-6" lower deck; 53'-0" OAL
Deck section width	8'-6"
Crossmembers	4" I-beam on 9" centers
Loaded deck height	38" (+/-)
Flooring	1-1/2" (nominal) apitong secured with deck screws full width
Outriggers	None
Gooseneck/deck connection	Fixed with pivot
Deck/rear bridge connection	Sliding bogey
Load securement	Tie downs - Double key hole chain slots upper flange on 45" centers. Double key hole slots down center of deck 3/8" steel. Four chain holes across rear approach plate
Rollers	3-3/4" x 18" cable roller centered in front of lower deck
Expanded metal	Beneath all center chain slots
Additional deck specifications	None

3. REAR BRIDGE

Number of axles	3
Axle spacing	50"
Axle capacity	25,000#
Brakes	12-1/4" x 7-1/2" S-cam air actuated with spring brakes on all axles
Anti-lock brake system	Two (2) sensor, one (1) modulator system
Wheels	Eight (8) stud; 6.75 x 17.5 steel disc hub piloted system with oil seals; inner wheels steel with outer aluminum wheels polished inside of outside wheel
Rims	None
Tires	Twelve (12) 235/75R17.5 (H) 16PR radials
Suspension	Ridewell air
Exhaust Valve	Right Weigh scale gauge mounted in box on driver's side of gooseneck
	None

Suspension options	1) Stop and alignment bracket for bogey at rear of trailer. 2) DO NOT grease flanges for suspension rollers.
Dock levelers	None
Additional rear bridge specifications	None
4. GENERAL	
Lights and wiring	12 volt LED lights with Phillips wiring system with 3 extra marker lights per side
Paint	Standard Talbert black
Remote trailer operation	6 Channel for winch, tilt and axle operations
Bumper	Heavy duty DOT approved
Mudflaps	Anti-sail
Additional general specifications	Conspicuity markings to meet DOT specifications

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.