

HALE

TRAILER

BRAKE & WHEEL



A021957
VIN: 43788

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: 4053TA
Capacity in tons: 40

Gooseneck design	LP Fixed
Upper deck length	11'-9"
Loaded 5th wheel height	48"
2 Swing radius	96" with 18" kingpin setting
	Break-away kingpin/5th wheel plate
Planetary winch	Recessed 20,000# hydraulic planetary winch with air clutch, air tensioner, four (4) roller fairlead and 105' of 5/8" diameter cable with tail chain and hook
Power source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Electrical receptacle	Seven pin connector
Tool Box	Updated design for both sides with weatherproof seals
Landing gear	2 speed Holland with crank on driver's side
Auxiliary Air Reservoir	Yes
Additional gooseneck specifications	None
Deck section design	Four beam
Deck section length	41'-3" lower deck; 53'-0" OAL
Deck section width	8'-6"
Crossmembers	4" I-beam on 9" centers
Loaded deck height	36" (+/-)
Flooring	1-1/2" (nominal) apitong secured with deck screws full width
Gooseneck/deck connection	Fixed with pivot
Deck/rear bridge connection	Sliding bogey with larger diameter push/pull cylinders
Load securement	Tie downs: Double key hole chain slots in side beam upper flange on 36" centers. Double key hole chain slots down center of deck on 36" centers. Eight (8) key hole chain slots across rear approach plate
Rollers	3-3/4" x 18" cable roller centered in front of lower deck
Expanded metal	Beneath all center chain slots
Additional deck specifications	1) - Flip-up step with traction surface on each side of the deck towards the front with spring loaded latch, includes handles on gooseneck each side 2) - 1 1/2" x 2" Solid rails on 56 1/2" gauge on lower deck and through rear tail (customer to supply pictures)
Number of axles	2
Axle spacing	50"
Axle capacity	25,000#
Brakes	12-1/4" x 7-1/2" S-cam air actuated with spring brakes on all axles
Anti-lock brake system	2 sensor, 1 modulator system
Wheels	Eight (8) stud; 6.75 x 17.5 aluminum/steel disc hub piloted system with oil seals; inner wheels steel with outer aluminum wheels polished
Tires	Eight (8) 235/75R17.5 (H) 16PR radials PSI Tire inflation system

Suspension	Ridewell air with Air Weigh QuickWeigh scale mounted in tool box on driver's side near controls
Exhaust Valve	Manual
Suspension options	1) - Stop and alignment bracket for bogey at rear of trailer. 2) - DO NOT grease flanges for suspension rollers. 3) - Air and electrical ran in metal E-Chain, sized for future dock levers
Dock levelers	None
Additional rear bridge specifications	None
Lights and wiring	12 volt LED system including mid-turn lights, license plate light regular 11 marker lights each side including mid-turn light Strobe lights with switch in rear bumper
1 Paint	Special color Ford Vermillion Red 6886/F1, Valspar urethane no. F63RL0317, R-Cure 800 series paint with zinc rich primer matched to a customer supplied paint (NON-METALLIC)
Remote trailer operation	6 channel to operate winch, tilt and axles
Bumper	Heavy duty DOT approved
Mudflaps	Anti-sail
Additional general specifications	1) Conspicuity markings to meet DOT specifications 2) Centralized Lube System 3) Capacity: 80,000# Distributed; 50,000# in 10'-0"

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.