

# XL SPECIALIZED TRAILERS

# XL 110 Low-Profile HDG: 15" Deck Height, 4 BEAM

OVERALL LENGTH OVERALL WIDTH CAPACITY WEIGHT +/- 3%

61' 6" 102" 110,000 LB DISTRIBUTED; 100,000 LB IN 16 0,000 LB

#### GOOSENECK

NECK STYLE LENGTH KINGPIN SETTING SWING CLEARANCE **5TH WHEEL HEIGHT** HYDRAULICS

LOW-PROFILE SCRAPER 14' 16" 122" 51" W/ 5 VARIABLE RIDE HEIGHT POSITIONS 13 HP HONDA, DUAL HYDRAULICS, W/ STEEL COVER BRACKETS FOR POWER UNIT WORK LIGHT ON NECK

# MAIN DECK

CROSSMEMBER

OUTRIGGERS

CHAIN DROPS

BEAMS D-RINGS

LENGTH

AXLES

ABS

TIRES

WHEELS

BRAKES

DRUMS

DECKING

D-RINGS

CHAIN DROPS

ELECTRICAL

SUSPENSION

AXLE SPACING

LENGTH LOADED DECK HEIGHT DECKING

29

15" W/ 4" GROUND CLEARANCE 1 3/8" APITONG DECKING, RAISED - CENTER OPEN DO NOT SECURE THE DECKING. CUT INTO PLACE AND SHIP LOOSE 6" AND 4" STUBBED JR. I-BEAM ON 12" ALTERNATING CENTERS (4) 11" FAB BEAMS (7) BENT D-RINGS PER SIDE SWING OUT OUTRIGGERS - 24" CENTERS - H.D. FLAT BACK FRONT 24" CENTERS - OUTSIDE BEAMS

## **REAR DECK**

18' 6" WITH 32° REAR TRANSITION LOADED DECK HEIGHT 40" (4) 25,000 LBS. NOMINAL (5/8" WALL) HENDRICKSON / 25,000 CAPACITY/ AIR RIDE 54 1/2" N/A SPRING BRAKES ON (1) AXLE 255 / 70R / 22.5 ( H ) 8.25 X 22.5 10-HOLE PILOT MOUNT STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC 16 1/2" X 7" OUTBOARD 12V SEALED GROTE SYSTEM WITH ( 3 ) TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE WITH SWITCH TO MAKE 3RD TAIL LIGHT OPEN WHEELS BOLSTER STYLE, OPEN BOOM TROUGH BOLSTERS DROPPED 4" DOWN (2) FLAT D-RINGS AT REAR ON MAIN BEAMS (2) CHAIN DROPS PER BOLSTER STAKE POCKETS (2) STAKE POCKETS AT REAR

#### PAINT

BLACK

ADDITIONAL

MANUAL RIDE HEIGHT CONTROL NO PREP FOR FLIP AXLE RAISE AND LOWER VALVE BUCKET WELL AT REAR OF MAIN DECK WITH PLATE ON BOTTOM WITH 4 FLAT D-RINGS TOOL BOX IN FRONT OF MAIN DECK WITH 4 FLAT D-RINGS (2) PAIR OF FLAG HOLDERS FRONT RAMP UPPER FLANGE REINFORCEMENT AIR LIFT AXLE ON 4TH AXLE LIQUID FILLED AIR GAUGE 31" FRONT FLIP RAMPS

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.