

# HALE

## TRAILER

### BRAKE & WHEEL



**A021964**  
**VIN: 000415**

**SALES | RENTALS | PARTS | SERVICE**

<b>Allentown, PA:</b> 800-383-8894	<b>Jacksonville, FL:</b> 800-828-3055
<b>Baltimore, MD:</b> 888-601-7500	<b>Little Rock, AR:</b> 833-424-8944
<b>Boston, MA:</b> 800-854-5310	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Richmond, VA:</b> 866-839-3495
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Base Weight:** 11,220

### 22.5ART 22.5 Ton Tandem Air Tilt/Air Ramp Tags

#### TRAILER

**Overall Length** 34 ft. 6 in.  
**Overall Width** 102 in.  
**Weight lbs +/- 2%** 11100, including options  
**A-Frame** 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam  
**Hitch** 3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

#### DECK

**Deck Length** 21 ft.  
**Loaded Deck Height** 34 in.  
**Main Frame** Hi-Tensile Wide Flange 14 in. @ 26  
**Cross Members** Hi-Tensile 6 in. Channel @ 8.2  
**Side Rail** Hi-Tensile 8 in. Channel @ 11.5 open on inside  
**Air Tilt Deck** 4 Air Bags  
**Floor** 1 3/8 in. x 7 in. Keruing Shiplapped  
**Landing Gear** Dual 2 Speed  
**Step** \*NPO\*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

#### SUSPENSION/AXLES

**Axles** 25,000 lbs Capacity 77.5 in. Track  
**Spread** 49 in.  
**Suspension** Heavy Duty spring ride  
**Alum Air Tank** \*NPO\*: Drain plug with cable  
**Brakes** Quick Change 12 1/4 in. x 7 in.  
**Brake Chamber** #3030, All Axles  
**Air Brake System** 2S/1M  
**Air Tank(s)** Aluminum  
**Bearings** Oil Bath  
**Slack Adjusters** Automatic  
**Hubs & Drums** 8 Stud Unimount C / W Cast Drums  
**Tires** 235/75R17.5 16 ply  
**Wheels** Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)

#### BEAVERTAIL

**Length** 6 ft. @ 6 degree slope, Planked in

#### RAMPS

**Length** 38 in. x 76 in. Air Operated Planked  
**Brackets** \*NPO\*: To hold ramp brace when not in use, 1 per side

#### GENERAL SPECIFICATIONS

**Electrical System** Modular, Vapor Proof GROTE Ultra Blue  
**Lights** LED CMVSS 108 / FMVSS 108  
**Lights** Amber Flashing Strobe Lights(Mounted in Ramps)  
**Strobe Wiring** \*NPO\*: Switch to be located in toolbox

**Base Weight:** 11,220

**GENERAL SPECIFICATIONS**

<b>Front Connector</b>	SAE J560 7 Pin
<b>Finishing</b>	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
<b>Color</b>	Black
<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and cover
<b>Load Securement</b>	8 pair of D-rings: 5 pr on main deck, evenly spaced, 1 pr on B/T, 1pr. On main beam at headboard, 1 pr on top of a frame top flange eachside of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.