



Resale Inventory A021968 VIN: 518723

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: Jacksonville, FL: 800-828-3055 800-383-8894 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: Richmond, VA: 866-839-3495 800-438-2250 Delmar, DE: Scranton, PA: 866-486-1400 800-569-1400 Des Moines, IA: Springfield, MA: 888-673-5011 800-854-5306 Voorhees, NJ: Elkton, MD: 800-544-7127 866-315-0235

HaleTrailer.com | @haletrailer f 쭞 🛅 🎯 🛗

800-232-6535 *FIN.

5 *FINANCING AVAILABLE

A. DESIGN INFORMATION

Overall length 48ft

Capacity 80,000# Distributed frame capacity-GAWR and tire

ratings determine legal payloads

Framework Hi-Tensile Steel flanges and webs with Structural Steel Siderails

Width 102 in.

B. PLATFORM

Kingpin 36 in. kingpin setting with sloped upper coupler plate

Loaded fifth wheel height 49 in Loaded fifth wheel height

Flooring 1-1/8 in. apitong; (2) 5/16 in. fasteners per board per crossmember

Side Rails 6 in.@ 8.2# All Steel Structural Channel Rubrail 3/8 in. x 3 in. Rubrail with 4 in. deep pocket

Main Beams Hi-Tensile steel fabricated I-Beam, top and Bottom flanges

3/8 in. x 5in(min 130)

Stake Pockets Steel on 24 in. c/c on sides; weld on B.N.;5 pockets on rear. Double

Pipe spools located between pockets on sides and rear

Crossmembers Single piece full width (except in neck area) 4 in. x 3.19# All Steel I-beams

on 12 in. c/c

Bulkheads 48 in. high steel, no turnback 102 in. wide

Bulkhead Connection Welded-F5 Type.

Landing gear Binkley 51000 2 speed, square leg with 10 in square cushion foot and fabricated bracing

Knee Braces (5) pair Formed with triangular cut-outs

C. UNDERCARRIAGE

Number of axles 2

Axle 5/8 in. wall with tapered spindle

Axle spread Closed Tandem 49 in.

Suspension Tandem Axle Air Ride Slider AAZNT (60 in. Slide Range)

Dump Valve Auto Glad Hand Air Bag Dump Wheels 8.25 x 22.5 - 10 Hole Steel Disc