

HALE

TRAILER

BRAKE & WHEEL



A022026
VIN: 000417

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Weight: 11,000

25FDNT 25 Ton Tridem Flat Deck Non Tilt Tags

TRAILER

Overall Length	31 ft. 1 in.
Overall Width	102 in.
Weight lbs +/- 2%	10803, including options
Hitch	*NPO*: 3 in. Pintle Eye, Adjustable 5 Position, 29 in. - 38 in.

DECK

Deck Length	24 ft.
Loaded Deck Height	*NPO*: 40 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 22
Cross Members	Hi-Tensile 6 in. Channel @ 8.2
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
Rub Rail	5/16 in. x 2 in. Moulded Rub Rail
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	Dual 2 Speed
Stake Pockets	Std Highway Pockets - 48 in. O/C
Bumper	Standard ICC with Tow Hooks
Step	Bolt on, Located on Front Corner of deck, Driver side

SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track
Spread	49 in.
Suspension	Heavy Duty spring ride
Brakes	*NPO*: 16-1/2 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	*NPO*: 10 Stud, Long Stud c/w Cast Drums
Tires	*NPO*: 255/70R22.5
Wheels	Alum. Wheel Pkg. 22.5 (6 Machined, 6 polished)

GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Front Connector	SAE J560 7 Pin
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color	Black
Mudflaps	1 set of BWS at rear
Load Securement	Optional
Toolbox	Full A Frame mounted with solid bottom and cover
Fenders	*NPO*: Heavy Duty Fenders, No Grouser Bars

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.