

HALE

TRAILER

BRAKE & WHEEL



A022027
VIN: 000413

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Base Weight:	18,540	53ET3XP 53 ft. Tridem Paving & Recovery
TRAILER		
Overall Length	53 ft.	
Overall Width	102 in. (Over width permits may be required)	
Weight lbs +/- 2%	19759, including options	
Spacing	*NPO*: King pin to center of rear axle not to exceed 42 ft 11 in.	
GOOSENECK		
Coupler	Weld in King Pin	
Coupler Plate	5/16 in. Hi-Tensile, 48 in. Height	
Coupler Location	18 in.	
Length	10 ft. 6 in.	
Cross Members	Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C	
Swing Clearance	83 in.	
Floor	1 1/8 in. Shiplapped Apitong/Keruing	
Web	1/4 in. Hi-Tensile	
DECK		
Deck Length	35 ft. 1 in.	
Loaded Deck Height	35 in.	
Main Frame	3/8 in. x 5 in. Top Flange and 1/2 in. x 5 in. Bottom 100 KSI	
Cross Members	Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces	
Side Rail	6 in. @ 8.2 Channel	
Web	3/16 in. Hi-Tensile	
Landing Gear	Dual 2 Speed	
Floor	1 3/8 in. Shiplapped Apitong/Keruing with 3/16 in. Deckplate over the wheels	
In Floor Chain Box	1 - located at rear of Gooseneck, 1 - located at rear of main deck, with deckplate covers included	
SUSPENSION/AXLES		
Axles	25,000 lbs Capacity	
Air Lift	Air Lift c/w Control Box: lead axle	
Spread	*NPO*: 60 in.	
Suspension	Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure	
Brakes	Quick Change 12 1/4 in. x 7 in.	
Brake Chamber	#3030, All Axles	
Air Brake System	2S/1M	
Air Tank(s)	Aluminum	
Slack Adjusters	Automatic	
Camshafts	28 Spline Non Enclosed	
Hubs & Drums	8 Stud Unimount C / W Cast Drums	
Tires	Tire Upgrade to 245/70R17.5 Continental HTL2 ECO	
Tire Inflation	*NPO*: Meritor System, Included	
Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)	

RAMPS	Length	6 ft. @ 8 degree slope, Planked
	Rear	45 in X 11 ft. Air Operated Bi Fold - Planked
	Main Deck to G/N	12 ft. Inset Full width Air Operated - Planked
	Main Deck to G/N	*NPO*: Ramp Prop Access Covers
GENERAL SPECIFICATIONS		
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Lights	LED CMVSS 108 / FMVSS 108
	Front Connector	SAE J560 7 Pin
	Rear Connector	4 Pin Plug
	Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
	Color	Black
	Mudflaps	1 set of BWS at rear
	Load Securement	* Moulded Rub Rail, Stake Pockets and Spools 24 in. OC (Over all Width affected by option as shown)
	Load Securement	15, Pair of in Floor Flush Mounted D-Rings: 3 pr GNK; 2 pr B/T; start directly aftr front ramp - 10 pr main deck, evenly spaced

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.