

## X-L SPECIALIZED TRAILERS, INC.

					OAL: 53'
MODEL:	XL 110HDE	<b>DIST:</b> 110,000#	CONC.	90,000# IN 10' CLOSE	OAW: 102" D
VIN#	4U3J05331GL0				GHT +/-3% 0
GOOSE	NFCK-				
LENGTH:		10' 5" NARROW NECK			
KING PIN SE		16"			
SWING CLE	-	84"			
511 WHEEL HEIGHT: 52" W/ 7 VARIABLE RIDE HEIGHT POSITIONS					
HYDRAULICS: 13 HP HONDA UNIT					
FLIP NECK:		36" FLIP NECK WITH FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL			
MAIN DE	ECK-				
LENGTH:		28' 7" EXTENDING TO 49' 5"			
LOADED DECK HGT:		24" W/ 6" GROUND CLEARANCE			
DECKING:		1 1/8" APITONG DECKING, FLUSH, CENTER COVERED			
CROSSMEMBER: 6" JR. I-BEAM ON 12" ALTERNATING CENTERS					
SIDE BEAMS: FAB I-BEAM					
D-RINGS: 10 BENT D-RINGS PER SIDE TOTAL OF 20 - STAGGER BETWEEN CHAIN DROPS					
OUTRIGGER	S:	REMOVABLE SWING OUT OUTRIG	GGERS - 24"	O/C	
CHAIN DROP	PS:	(10) CHAIN DROPS PER SIDE -	OUTSIDE BEA	MS ONLY - STAGGER BE	ETWEEN D-RINGS
REAR D	<u>ECK:</u>				
LENGTH:		14'			
LOADED DECK HEIGHT: 36"					
AXLES: ( 3 ) 25,000 NOMINAL, 77 1/2" TRACKING,					
SUSPENSION:		HEND-TURNER/25,000 AIR			
AXLE SPACING:		54"			
ABS: N/A WITH SPRING BRAKES ON 1 AXLE					
TIRES: MICHELIN 245/70R/17.5					
WHEELS: 6.75 X 17.5 ALUMINUM POLISHED OUT STEEL IN DISC WHEELS					
BRAKES: 12 1/4" X 7 1/2"					
DRUMS:		HUB PILOT/ OUTBOARD DRUMS			
ELECTRICAL:		12V SEALED GROTE SYSTEM WI	TH 3 TAILLIGH	IT ALUMINUM PACKAGE	
DECKING:		REMOVABLE RAISED WHEEL CO	VERS BOLSTE	R STYLE WITH OPEN B	DOM TROUGH
D-RINGS:		2 BENT D-RINGS IN TAIL CHANNE			
ADDITIC	NAL:	(5) TOTAL CLEARANCE LIGHTS	PER SIDE - LE	D	
PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER					
		ONE PAIR OF FLAG HOLDERS IN	-		
		RAISE AND LOWER VALVE			
		31" FRONT FLIP RAMPS			
		FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR TWO AXLE BOOSTER			
		4" AMBER STROBE LIGHT TO BE	USED AS 3RD	TAIL LIGHT	
		LED LIGHTING - STANDARD			
		LIQUID FILLED AIR GAUGE			
		CHAIN UP AXLE ON 3RD AXLE WITH DUMP VALVE			
		MANUAL RIDE HEIGHT CONTROL	-		
		EXTENSION STOPS 24" O/C			

DISCLAIMER