

# HALE TRAILER

BRAKE & WHEEL



A022183  
VIN: 74302

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Order

### Infinity Drop Deck 53' Tridem Air Ride (Model: HAICD22TAF)

<b>Length / Width:</b> 53 feet x 102 inches	
<b>Suspension Type:</b> Tri-axle air	
<b>Deck Lengths:</b> 11 feet front and 42 feet rear	
<b>Frame Rating:</b> 100,000 lbs distributed - GAWR and tire ratings determine legal payloads	
<b>Rear Deck Height:</b> 40 inches - loaded	
<b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips	
<b>Crossmembers:</b> 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
<b>Single Coil Hauling Package:</b> Included	
<b>Side Rails:</b> Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact	
<b>Chain Cargo Tie Downs:</b> 17 pair recessed in siderails	
<b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
<b>Rubrail:</b> Integrated with siderail	
<b>Main Beams:</b> 130K load bearing flanges	
<b>Kingpin:</b> 30 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkhead Pockets:</b> 4 DOT type bulkhead pockets only - welded to front	
<b>Bulkheads:</b> Removable aluminum 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets	
<b>Number of Axles:</b> 3	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 61 inches, 61 inches - set ahead to 40 feet CL Kingpin to CL Tridem	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 steel disc inside wheels - 6 aluminum Lvl One buffed outside	
<b>Tires:</b> 255/70R 22.5 16PR - quantity 12 OEM standard	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> AANL23K Intraax air ride	
<b>Auto Glad Hand Dump:</b> Installed	
<b>Electric Dump Valve:</b> Wired to 7-way auxiliary socket to dump rear axle	
<b>Air Lift:</b> (1) UBL installed on center axle; Includes additional leveling valve to fully raise lower deck when lifted for additional tire ground clearance; NOTE: Axle to be lifted only when trailer is unloaded	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear - STANDARD	
<b>Paint:</b> Fontaine Red urethane on steel parts with Infinity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements - painted steel	
<b>Mudflaps:</b> 1 set OEM standard behind rear axle	
<b>Winch Track:</b> Full length integrated double L type aluminum on both sides where possible -- STANDARD	
<b>Sliding Winches:</b> 12 total, 2 front deck and 10 rear deck: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD	
<b>27 foot Winch Straps:</b> None standard	
<b>30 foot Winch Straps:</b> None standard	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Spare Tire Carrier:</b> 1 standard - mounted between lower gooseneck beams at drop	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> Install registration holder - OEM standard	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.