



A022286

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Boston, MA: 800-854-5310 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: Scranton, PA: 866-486-1400 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: Voorhees, NJ: 800-544-7127 866-315-0235

HaleTrailer.com | @haletrailer f 🎔

800-232-6535 *FINANCING AVAILABLE

XL 120 Step Deck Extendable

OVERALL LENGTH 53'
OVERALL WIDTH 102"

CAPACITY 120,000 LB DISTRIBUTED; 100,000 LB IN 10' CLOSED

WEIGHT +/- 3% 0,000 LB

GOOSENECK

LENGTH 11' 6" NARROW GOOSENECK

KINGPIN SETTING 16" REMOVABLE

 SWING CLEARANCE
 102"

 5TH WHEEL HEIGHT
 52"

 DECKING
 NONE

 STAKE POCKETS
 NONE

LANDING GEAR 2 SPEED W/ HANDLE ROAD SIDE FLIP NECK PREP FOR 72" FLIP NECK 72" FLIP NECK

72" FLIP NE

MAIN DECK

 LENGTH
 41' 6" EXTENDING TO 64' 4"

 LOADED DECK HEIGHT
 33" WITH OPEN WHEELS

 DECKING
 1 1/8" APITONG DECKING, FLUSH

 CROSSMEMBER
 4" JR. I-BEAM ON 12" CENTERS

BEAMS 6" MILLED SIDE RAILS

 STAKE POCKETS
 24" CENTERS WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS

 D-RINGS
 (7) PAIR OF PAN STYLE D-RINGS ON MAIN DECK - EVENLY SPACED

(7) PAIR OF FLAT D-RINGS AT BOTTOM KNEE BRACES

 AXLES
 (3) 25,000 LBS. NOMINAL, (5/8" WALL)

 SUSPENSION
 HENDRICKSON / 25,000 CAPACITY / AIR RIDE

AXLE SPACING 60

ABS NA WITH SPRING BRAKES ON (1) AXLE

TIRES MICHELIN 245 / 70R / 17.5 (H)

WHEELS 6.75 X 17.5 8-HOLE, PILOT MOUNT, STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC

 BRAKES
 12 1/4" X 7 1/2"

 DRUMS
 OUTBOARD

ELECTRICAL 12V SEALED GROTE SYSTEM WITH (3) TAILLIGHT ALUMINUM PACKAGE

4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT

D-RINGS (1) PAIR OF BENT D-RINGS IN TAIL CHANNEL

PAINT BLACK

ADDITIONAL RAISE AND LOWER VALVE LOCATED IN REAR DRIVER SIDE BOLSTER

LIQUID FILLED AIR GAUGE LOCATED IN REAR DRIVER SIDE BOLSTER (1) PAIR OF EXTRA CLEARANCE LIGHT AT START OF MAIN DECK

DUST SHIELDS

PREP FOR 2 AXLE POWER BOOSTER
MANUAL RIDE HEIGHT CONTROL

(1) 4-WAY PLUG IN EACH CORNER OF MAIN DECK (1) 4-WAY PLUG IN REAR BOLSTER - BOTH SIDES

LIMIT CHAINS ON ALL 3 AXLES

PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES

SIMILAR TO 23527