		SALES	RENTALS	PARTS	SERVICE
		Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
		Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
TRAI	LER	Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
BRAKE &	WHEEL	Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Talbert ® SINCE 1938		Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
		Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
	A022302	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
	VIN: 43981	HaleTrailer	.com @hale	trailer f 🎔	
		800-232	2-6535 *	FINANCING	AVAILABLE

Model: Axle Attachment

Capacity in tons: 55 **1. DESIGN PARAMETERS** Flip-up & removable Type Framework Fabricated **1** Suspension 30,000# Capacity Ridewell air Axle attachment connections Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections 25,000# - GAWR 24,700# Axle capacity 16-1/2" x 7" air actuated Brakes Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil Wheels seals, inner wheels steel with outer aluminum wheels polished Anti-lock brake system None Tires Four (4) 275/70R22.5 (H) 16PR radials 8'-6" Bridge width Axle frame height 41" frame; 37" bolster Half bolster With flag holder slots Lash rings 2 at rear bent style 12 volt system with the following: Lights and wiring All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style 4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up Paint Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer Mudflaps Talbert anti-sail Additional design specifications 1) 2 rubber bumpers on top 2) 54" axle spacing 3) Over ride chains 4) Estimated empty weight: 2,850# **1** Compatibility With existing Talbert Trailer, 60SA or 60CC