

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A022338
VIN: 018042

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

X-L SPECIALIZED TRAILERS, INC.

MODEL: XL 120JPS
 WEIGHT +/-3% 19175

DIST: 120,000

OAL: 40' 6"
 OAW: 120"

3 AXLE JEEP

GOOSENECK-

LENGTH: 13'
 KING PIN SETTING: 16" 40"
 SWING CLEARANCE: 120" 96"
 5TH WHEEL HEIGHT: 52"
 D-RINGS: 3 PAIR OF BENT D-RINGS
 LANDING GEAR: 2 SPEED LANDING GEAR, HANDLE ON DRIVER SIDE
 DECKING: FULL WIDTH STYLE WITH 1 1/8" APITONG DECKING FLUSH
 STORAGE COMPARTMENT IN JEEP GOOSENECK TO STORE LIGHT ITEMS

REAR DECK:

12' 3" MAIN DECK LENGTH, 15' 3" WHEEL AREA LENGTH
 10' WIDE
 5TH WHEEL HEIGHT: SLIDING HYDRAULIC HAT BOX
 BUNK: 10' WIDE BUNK WITH 2 PAIR OF D-RINGS
 LOADED BUNK HEIGHT: 36" TO 42"
 AXLES: (3) 25,000 NOMINAL, 95 1/2" TRACKING
 SUSPENSION: HEND-TURNER / 25,000 AIR
 AXLE SPACING: 60"
 ABS: N/A , SPRING BRAKES PER 1 AXLE
 TIRES: 245 / 70R / 17.5
 WHEELS: 6.75 X 17.5 STEEL INSIDE, POLISHED OUTSIDE DISC WHEELS
 BRAKES: 12 1/4" X 7 1/2"
 DRUMS: OUTBOARD
 ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT PACKAGE
 D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL
 RAISE AND LOWER VALVE
 D-RING IN BETWEEN EACH AXLE

ADDITIONAL:

PAINT: ADAPTER TO ACCEPT 102 WIDE FLIP AXLE FROM 120SDE
 BLACK
 FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR PIN ON AXLE
 13HP HONDA POWER UNIT MOUNTED AT FRONT OF JEEP
 PINTEL HITCH AT REAR
 MANUAL RIDE HEIGHT CONTROL VALVE - BOTH LEVELING VALVES
 2ND LEVELING VALVE
 DOUBLE DROP STYLE JEEP

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.