

Model	TANDEM	ABS	4S / 2M	Tire Carrier	ONE - P/S ACCESS
Beam Mat'l	16" STEEL @ 31 # / FT			Landing Gear	2 SPEED JOST A450
Length	34'				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-265		X-MBR ONLY FOR 3RD AXLE		
Chassis Neck	STD		HT250	Elec Coupler	7 WAY
King Pin Setting	18"		Distance: 103"		
5th Whl Plate	1/2" W/ 3/8" MOUNT		From: REAR AXLE	Hyd Tank	NONE
5th Whl Ht	49"			Hyd Hose Fitting	WINGNUT
Overhang	6"	Controls		Hyd Hose Length	108"
Rear Axle Setting	21-1/2"			Tow Hooks	NONE
K/P To Rear Axle	368-1/2"			Paint	EAST BLACK BODY
Suspension	WATSON SM-60 SP	Location			EAST BLACK FRAME
Susp Control	NONE	Axle(s)		Tarp Bar Tape	NONE
Susp Spacing	STD				
Susp Options	NONE	Accessories		Chassis	
Springs	SM-60 60,000#			Options:	
Axles	TP SPINDLES	Brakes			
Accessories	25K - RATED (3)	Drums			MUDFLAP ON CHASSIS
Brakes	16-1/2" x 7"	Hubs			
Drums	CAST				
Hubs	10 STUD STEEL - PILOTED	Wheels			
Wheels	8.25 x 22.5 8 STEEL	Tires			
Tires	295/75R 22.5 RA 16 PLY GEN				

1. NO CENTER BOLSTER	
2. TARP HOOKS: BURNOUT DESIGN-REF 54643 FOR LOCATIONS - 8 EACH SIDE + 4 FRONT & 4 REAR	WEIGHT: 20,557
3. 25,000 # - RATED LONG STROKE CHAMBERS AND SLACKS	CHANGE 1
4. ANGLE IS ON TOP OF TOP RAIL-NOT FLUSH WITH BULKHEAD OR TAILGATE.	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.