



A023020
VIN: V7503

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Capacity Concentrated	110,000 lbs. Open in 2 point rigid load base 110,000 lbs. in 16' Closed	
OAL	53' OAW 102" 58' W/Options	
Gooseneck	10' 5" Hydraulic Detachable 51" 5th Wheel Height 15" King Pin 80" Swing Clearance 5 Position Ride Height Adjustment 3' Flip Neck Connection 3' Flip Neck(116" Swing) LED Work Light	Sub Frame 14' 1" Long 39" Loaded Deck Height 32 Degree Rear Transition Open Wheels with Bolsters Chain Slots in Each Bolster 2 Flat D-Rings at Rear Flag Holders 1 pair Stake Pockets in Tail Channel Frame Reinforcement for Single Axle Stinger
Main Deck	28' 7" Closed- 50' Open 14" Fabricated I-Beams 20" Loaded Deck Height 6" Ground Clearance Cross Members ALT on 12" Centers 8 Bent D-Rings per Side Chain Slots on 24" Centers each side 1 3/4" Apitong Raised Decking-Full Width Upper Flange Reinforcement Front Flip Ramps Full Depth Removable Swingout Outriggers Air Operated Lock Pin, Deck opens every 2' Toolbox W/Lid In Rear of Male Deck Section	Axles and Suspension 3 - 25,000 lb Axles 54 1/2" Axle Spacing Ridewell Suspension 16 1/2" x 7" Drum Brakes Spring Brakes on Two Axles Raise & Lower Valve Manual Ride Height Control Air Lift on 3rd Axle Airweigh Quickweigh Scale 255/70R22.5 Tires Suspension Controls in Bolster
Lighting	2 Tail Light Package with Stainless Steel Covers 2 Pr. Side Markers/1 Pr. Mid-Turn on Deck Grote Ultra Blue-Seal Wire Harness	



A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Gooseneck

13 hp Honda in base section/Dual Operation

Sub Frame

UHMW Poly Wheel Covers
275/70R22.5 tires
Polished Aluminum Outer Wheels
3rd tail light package with strobe (no battery)
Battery back for strobe with 4-way plug for FA
Drov Tire Inflation
Nitrogen Stinger Top Lugs
Subframe Disconnect

Main Deck

2 Pr Additional Clearance Lights
2 Pr Additional D-Rings
Fixed Front Ramps
33' 7" Closed to 60' Open
Tool Box in Front of Deck

Paint

Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.