



Resale Inventory
A023082
VIN: 35447

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

GENERAL:

Code: Non-Code
Product: Juice
Area of Operation:
Overall Length: 42' 6"

BARREL:

6400 gallons round, straight, cleanbore barrel. The barrel shall be made from 12 gauge T-304 stainless steel #4 polish, weld finish shall be W-0 outside, W-5 inside, 0 PSI operating pressure, 165 Degrees F.

HEADS:

Two (2) 12 Gauge T304 stainless steel #4 finish inside, West-Mark air dished and flanged

RINGS:

Stainless steel channel sections fully welded to the shell

BOLSTERS/WINGS:

Stainless steel construction, 5" tall

SIDE FILLERS:

Stainless steel coupler plate adjustment rails and kick plate

MANHOLE:

18" Stainless steel West-Mark with removable, cleanable gasket around collar

one (1) located top center prox, hinged at front

DECKPLATE:

One (1) Milk type stainless steel deckplate **with spilldam and drains**

VENTING:

(2) Olsen vents with **stainless steel nuts** located in manhole lid

INSULATION:

Barrel is insulated with 4" POLYISO foam sheets, fiberglass at heads, ring tape at all rings

JACKETING:

Belly wrapped 24 gauge stainless steel bright finish jacket with lapped seams, 20 gauge stainless steel heads, lock seamed to jacket

LADDERS:

Aluminum tubular with West-Mark heavy duty grated steps and 1" aluminum grab rails each side of ladder angled out at 45o from ladder bracket up approximately 48".

two (2) one located each side of deckplate

THERMOMETER:

NONE

LIGHTS:

12-volt 7-way vapor proof harness system.D.O.T. Trucklite LED lights and reflectors with center turn signals. Two (2) marker lights each side, one amber located 45o at front of front fenders and one red at side of rear light box. Molded main lead. Rear lights enclosed in stainless steel light boxes, (2) lights each box. Conspicuity striping at sides and rear head. Bett's PS-2 document holder on landing leg subframe, roadside.

FRONT RECEPTACLE:

7-way female receptacle and boot mounted on stainless steel bracket with glad hands for air hook-up

OUTLET VALVING:

One (1) Fort Vale 3" 3A sanitary milk valve at rear with stainless steel dust cover. Safety lock device on stem.

outlet, 90o to roadside, stainless steel apron under valve

PUMP PACKAGE:

NONE

LANDING GEAR:

JOST square leg, 2-speed, steel, sand shoes, 50,000 lb. lift, 160,000 lb. static load capacity
curbside crank handle

LANDING GEAR FRAME:

Frame to be stainless steel construction

LANDING LEG SUPPORTS:

Pipe style from leg up to crossmember and to rear

UPPER FIFTH WHEEL:

Heavy duty upper fifth wheel plate with kingpin, adjustable in 2" increments.

REAR SUBFRAME:

Stainless steel construction for a tandem axle semi

SUSPENSION:

Two (2) DANA - RF23 air ride integration system

AXLES:

Two (2) EATON 5 3/4" round x .375 wall, 71-1/2" track, MGM 3030 long stroke chambers, outboard mount Centrifuse drums, LMS aluminum hubs and cap with HUB piloted mounting, D22 spindles, Grease/synthetic, outrunner seals. Spicer silver non-asbestos brake lining and Gunitite automatic slacks. Tone rings for ABS system. Manual dump valve and Hadley height control valve.

TIRE MANAGEMENT SYSTEM:

None

BUMPER:

Stainless steel non-code 3" x 2" **Full width 95.5 long**

BRAKE SYSTEM:

To be built to D.O.T. specifications, BENDIX TABS 2S/1M ABS system. ABS malfunction/operation light located on center of roadside rear fender, facing forward, per D.O.T..

TIRES:

Eight (8) 275/80R 22.5 CONTINENTAL HTL

WHEELS:

Eight (8) 22.5 X 8.25 Aluminum machine finish, 10-hole, 11-1/4" bolt circle, HUB PILOTED.

CHAIN HOOKS:

Four (4) stainless steel chain hooks front side of rear subframe.

FENDER MOUNTING:

Stainless steel fender pipes with U-bolts and under straps

FENDERS:

Front and rear aluminum contour fenders, ribs down

MUDFLAPS:

Customer supplied

C.I.P.:

NONE

PAINT:

(1) Color IMRON 5000 SERIES, or equal, on all carbon steel parts.

color to be Black

TRANSPORT SECURITY SYSTEM:

Lugs for padlock security system at all (4) manhole lugs, Outlet valve and all openings. Drilled Manhole lug nut handles for seal tab cable

CALIBRATION:

Theoretical, in 1/4" increments, complete with charts

CERTIFICATION:

California Department of Food and Agriculture inspection and sticker

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.