

XL SPECIALIZED TRAILERS

XL 80 Slide Axle

OVERALL LENGTH 51' - CAL LEGAL

OVERALL WIDTH 102"

CAPACITY 80,000 LB DISTRIBUTED; 50,000 LB IN 10'

WEIGHT +/- 3%

GOOSENECK

LENGTH 10' 5" FULL-WIDTH NECK

KINGPIN SETTING SWING CLEARANCE 82" **5TH WHEEL HEIGHT** 49"

DECKING 1 3/8" RAISED APITONG

CHAIN DROPS 48" ON CENTER ON BOTH SIDES OF NECK

HYDRAULICS RUNS OFF WET KIT (15 TO 20 GPM HYD. REQUIREMENTS)

HYD. CONTROLS

STAKE POCKES

2 SPEED LANDING GEAR - HANDLE ON CURBSIDE LANDING GEAR

TOOLBOXES (2) TOOLBOXES RECESSED TOP OF NECK, WITH ALUMINUM LIDS AND PROP RODS

ROLLERS (1) RECESSED CABLE ROLLER

WINCH 20,000 LB HYDRAULIC WINCH, 100' OF 9/16" CABLE WITH LOOP

WINCH KICK OUT

ALL WINCHES ARE PLANETARY DRIVE STANDARD

MAIN DECK

LENGTH 40' 7" LOADED DECK HEIGHT 38"

DECKING 1 3/8" RAISED APITONG

CROSSMEMBER 4" & 3" JR. I-BEAMS ON 8" CENTERS

BEAMS (4) FABRICATED BEAMS

LOAD ANGLE 6 1/2" LOAD

STAKE POCKETS (1) RECESSED CABLE ROLLER **ROLLERS**

CHAIN DROPS 24" ON CENTER ON BOTH SIDES - DOWN CENTER

REAR DECK

(2) 25,000 LBS, NOMINAL (5/8" WALL) SUSPENSION HENDRICKSON / 25,000 CAPACITY / AIR RIDE

AXLE SPACING

ABS 2S1M WITH SPRING BRAKES ON (1) AXLE

TIRES 245 / 70R / 17.5 (J)

WHEELS 6.75 X 17.5 8-HOLE PILOT MOUNT ALUMINUM POLISHED OUT STEEL IN DISC BRAKES

12 1/4" X 7 1/2" WITH AUTO SLACK ADJUSTERS

DRUMS OUTBOARD

ELECTRICAL 12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT PACKAGE 4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT

BLACK **PAINT**

6 FUNCTION WIRELESS REMOTE **ADDITIONAL**

ENERGY CHAIN TO PROTECT AIR, ELECTRIC, AND HYDRAULIC LINES

MANUAL DUMP VALVE ON ALL AXLES LIMIT CHAINS ON BOTH AXLES

(1) FIXED-WELD ON STEP EACH SIDE ON BOTTOM OF OUTER BEAMS-FRONT OF MAIN DECK

AIR WEIGH DIGITAL SCALE

CHASSIS AUTO GREASE SYSTEM ON AXLES