

HALE

TRAILER

BRAKE & WHEEL



A023338
VIN: 44433

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-----------------|--------------|-------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Base Model #: DC40 x 102 Air Spread 22.5

Serial #: 44433

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 40'

TOP DECK-LGTH/HGT 10' Length = 59" Height

LOWER DECK-LGTH/HGT 30' Length = Front 41", Center 42" Rear 40" Heights

OVERALL WIDTH 8' 6"

KING PIN SETTING 18" - Squared Pickup Plate

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

FRONT SKIRT Steel Front with Bulkhead Pockets

REAR SKIRT Aluminum

BULKHEAD Removable Aluminum - 48" - No Side Return- 4 Posts DOT-(+145#) AB905

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sils-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/ 2 Nailer Boards

WINCHES 10 DOUBLE L

WINCH TRACK Double L Aluminum - Extruded Siderail C/S & R/S - Both Sides

TIE BAR D/S & C/S - Full Length Both Sides - 3/8" x 2"

STRAPS 10-4" Wide X 30' Strap w/Flat End Hook (+45#)

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles

SUSPENSION LOCATION Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer

AXLES (2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#) SCALES
None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)

TIRES 255/70R 22.5 - Firestone

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 5 Across Rear

SPOOL Triangular Shaped

RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced

CONTAINER TWIST LOCKS None

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

DUNNAGE RACK None
TOOLBOX MATERIAL None
TOOLBOX LOCATION None
LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS None
PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted
DECAL PACKAGE Standard Dorsey Logo Kit
CUSTOM 1. None
CUSTOM 2. None
CUSTOM 3. None
Reference SN # 44387

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.