

Model: Axle Attachment

Wheels

1 Paint

Mudflaps

1. DESIGN PARAMETERS

Flip-up & removable Type

Framework Fabricated Suspension Ridewell air

Axle attachment connections Attachment to be equipped with top and bottom connecting ears, pin tubes with

bolts and nuts, shims, chrome tapered connecting pins, air and electrical

connections

25,000# - GAWR 24,700# Axle capacity **Brakes** 16-1/2" x 7" air actuated

Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil

seals, inner wheels steel with outer aluminum wheels Dura-Bright

Anti-lock brake system

Tires Four (4) 275/70R22.5 (H) 16PR West Lake radials Bridge width

8'-6"

41" frame: 37" bolster Axle frame height With flag holder slots Half bolster 2 at rear bent style Lash rings

Lights and wiring 12 volt system with the following:

All lights to be LED excluding license plate light

Strobe lights with switch at rear

Wire for battery back-up Valspar standard Talbert red

Talbert anti-sail

1) 2 rubber bumpers on top

2) 54" axle spacing

3) Over ride chains

4) Estimated empty weight: 2,850#

Compatibility 4. GENERAL With existing Talbert Trailer, 55SA or 55CC

1 Change order notes

Additional design specifications

Changed paint to standard red