| | | SALES | RENTALS | PARTS | SERVICE |
|---------|------------------|-------------------|--------------|------------------|--------------|
| | | Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| | | Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| TRA | ILER | Concord, NC: | 800-438-2250 | Raleigh, NC | 833-418-9777 |
| BRAKE | & WHEEL | Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| | | Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| | Resale Inventory | Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| | A023622 | Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |
| Trailer | VIN: 051359 | | | trailer f Y | |
| | | 800-232 | 2-6535 * | FINANCING | AVAILABLE |

Frameless MVP SS

| Model # TNAR40NF720 | Weight | 12701 lbs. | *** | Cubic Yards | 71 | VIN # 5MADN4022LC051359 |
|--------------------------|--------|----------------------|-------|-------------|----|-------------------------|
| BODY | | | | | | |
| LOAD PROFILE | MA | TERIAL, 80K GVWR | | | | |
| LENGTH | 40 | | | | | |
| WIDTH | 102 | 2 | | | | |
| FLOOR | 1/4 | in. WITH 3/8 in.LAS | 10 F1 | Г. | | |
| CROSSMEMBER SPACING | 10 | IN. | | | | |
| SIDE PLACEMENT | OL | ITSET SMOOTHSIDE | PANE | EL | | |
| FLOOR LINER | NC | NE | | | | |
| VIBRATOR | NC | NE | | | | |
| RUBBER SEAL | YE | S | | | | |
| AIR FAIRINGS | NC | NE | | | | |
| WALL HEIGHT | 72 | | | | | |
| WALL THICKNESS | 4.5 | (100%) 2-1/4 in. SID | E PAN | ELS | | |
| WALL LINER | NC | NE | | | | |
| TOP RAIL OPTION | SC | LID | | | | |
| SOLID | | | | | | |
| REAR POCKET SLOPE | 2.7 | 5 | | | | |
| HOIST | 8-5 | 5-285 (41-42), CUSTC | M | | | |
| REMOTE GREASE | NC | NE | | | | |
| BULKHEAD | 3/1 | 6 IN. | | | | |
| BULKHEAD TYPE | RA | DIUS CORNERS | | | | |
| BULKHEAD DOOR | BU | LKHEAD DOOR, D.S | i. | | | |
| BULKHEAD SLOPE PLATES | NC | NE | | | | |
| LOWER BULKHEAD WRAP | NC |) | | | | |
| BULKHEAD STEPS | NC | NE | | | | |
| SIDES STEPS D.S. | LA | ST OUTSIDE ONLY | | | | |
| SIDES STEPS C.S. | NC | NE | | | | |
| SHOVEL HANGER | NC | NE | | | | |
| FRONT FENDERS WITH FLAPS | CC | RNER W/FLAPS | | | | |
| ALUMINUM ROLL CAP | NC | NE | | | | |
| | | | | | | |

| LIGHTS | |
|--------------------|---|
| LIGHT TYPE | GROTE L.E.D. W/ GROMMET |
| LIGHT PANEL | 4 LARGE-3 LARGE-4 LARGE (FULL LIGHT PANEL) OOOO OOO OOOO |
| APRON | 3/8 in. X 4 in. LIGHT SHIELD |
| STD. MARKER LIGHTS | 7 EACH SIDE |
| MID-TURNS | 1 PAIR L.E.D. (COMBO) |
| BACK-UP LIGHTS | NONE |
| AUXILIARY CABLE | 7 WAY (ISO) |
| BACK-UP LIGHT WIRE | NONE |
| | |

| ATE | |
|------------------------|------------------------------------|
| GATE SHEET THICKNESS | VERTICAL PANELS |
| GATE OPERATION | BALL VALVE |
| HINGE TYPE | O. S. SWING C.S. W/ GROUND CONTROL |
| COAL DOOR | 18 in. |
| CHUTE | NONE |
| GATE BRACING | NO BRACING (SMOOTH SIDE PANELS) |
| HALF ROUND ON GATE | NONE |
| ANGLE ON TOP OF GATE | NONE |
| SPREADER CHAINS | NONE |
| WINDERS / SAFETY LATCH | WINDERS (1) EACH SIDE |
| TARP HOOKS | NONE |
| GATE LINER | NONE |

| PRIMARY AXLES | |
|------------------------------------|---|
| MODEL | SPREAD TANDEM |
| NO. OF PRIMARY AXLES | 1 |
| SUSPENSION | HEND. INTRAAX AA-250 TP W/HXL-5 |
| AXLE SPACING | 122 |
| SUB-FRAME | WIDE I-BEAM (17 IN.) |
| AXLES | AXLE FOR INTRAAX ONLY. |
| BRAKES | 7 IN. XL, W/30-30 CHAMBERS |
| CAM GUARDS | YES |
| HUB AND DRUM | CAST W/STEEL HUB HP 10 STUD TP, LS, 7 IN. |
| TIRES | GENERAL RA 11 R 22.5 16 PLY |
| WHEELS | ALCOA ULTRA HP 22.5X8.25 10 HOLE CLEAN BUFFED |
| PRIMARY AXLE TIRE INFLATION SYSTEM | NONE |

| LIFT AXLES | |
|---------------------------------|---|
| NO. OF LIFT AXLES | 1 |
| LIFT AXLE SUSPENSION | HEND. INTRAXX AAL 25K (4) TIRES W/HXL-5 |
| LIFT KIT | HEND. UBL-002 (INTRAAX AAL) |
| LIFT AXLE DISTANCE | 122 |
| LIFT AXLE | AXLE FOR INTRAAX ONLY. |
| LIFT AXLE BRAKES | 7 IN. XL, W/30-30 CHAMBERS |
| LIFT AXLE HUB AND DRUM | CAST W/STEEL HUB HP 10 STUD TP, LS, 7 IN. |
| LIFT AXLE TIRES | GENERAL RA 11 R 22.5 16 PLY |
| LIFT AXLE WHEELS | ALCOA ULTRA HP 22.5X8.25 10 HOLE CLEAN BUFFED |
| LIFT AXLE CONTROLS | ELECTRIC UP THRU AUX. & BALL VALVE (NO/REG.) |
| FREE WHEEL VALVE | NONE |
| LIFT AXLE TIRE INFLATION SYSTEM | NONE |

STEERABLE LIFT AXLES

| NO. OF STEERABLE AXLES | 0 | |
|------------------------------|------|--|
| STEERABLE AXLE SUSPENSION | NONE | |
| STEERABLE AXLE DISTANCE | N/A | |
| STEERABLE AXLES | NONE | |
| STEERABLE AXLE BRAKES | NONE | |
| STEERABLE AXLE HUB AND DRUMS | NONE | |
| STEERABLE AXLE TIRES | NONE | |
| STEERABLE AXLE WHEELS | NONE | |
| STEERABLE AXLE CONTROLS | NONE | |
| | | |

| CHASSIS | |
|-------------------------------|----------------|
| PIN SETTING | 16 |
| 5TH WHEEL PLATE | BREAK-AWAY PIN |
| 5TH WHEEL PLATE HEIGHT | 49 IN. HIGH |
| TRACTOR DRIVE MODEL | TANDEM DRIVE |
| GALVANIZED SUSPENSION HANGERS | YES |
| DRAFT ARM | 3/8 ALUM |

SUSPENSION CONTROL

| DUMP REAR AXLE SEPARATE THRU A | UX. |
|---------------------------------------|---|
| ABS FOR TRAILER | (1) 2S1M MERITOR / WABCO |
| SLACKS | AUTOMATIC |
| AXLE LUBRICATION | HXL, SYNTHETIC SEMI-FLUID GREASE |
| HUBODOMETER | NONE |
| DUST COVERS | NONE |
| TIRE CARRIER(S) | NONE |
| DOLLIES - LANDING GEAR - LANDING LEGS | JOST A450 - (62,500 lb.) - 10 YEAR NO LUBE - STEEL - D.S. |
| REGISTRATION HOLDER | NONE |
| AIR GAUGE / SYSTEM | YES, IN FRONT |
| ENCLOSURE FOR SWITCHES | STAINLESS STEEL |
| AIR TANKS | ALUMINUM TANK |
| HYDRAULIC HOSE FITTING | 1in. X 108 in. HOSE W/WING FITTING |
| FLAPS FRONT OF TIRES | 30 in. BUFFED ALUM/12 in. RUBBER FULL ACROSS FRONT OF EACH AXLE |
| INSTALL CENTER FLAP BEHIND FRON | TAXLE |
| FLAPS REAR OF TIRES | 30 in. BUFFED ALUM./12 in. RUBBER BEHIND FRONT AXLE, FULL ACROSS REAR OF TRAILER |
| TOW HOOKS | (2) BOLT ON |

TARP TARP MANUFACTURER NONE TARP CONTROL NONE TARP COLOR NONE BOW HOLDERS NONE TARP BRACKET NONE

| GALVANIZED |
|-----------------|
| BLACK SOFT COAT |
| BLACK |
| BLACK |
| BLACK |
| BLACK |
| MAC BLACK |
| NONE |
| |

| ACCESSORIES | |
|-----------------------------------|------|
| NO. OF CHAIN TIE DOWNS (PER PAIR) | NONE |
| (CUSTOMER MUST SPECIFY LOCATION) | |
| TOW MOTOR PACKAGE | NONE |
| COIL RACK ANGLES | NONE |
| LOAD LEVEL INDICATOR | NONE |
| 3-1/2 IN. ANGLES UNDER RAIL | NONE |

DISCLAIMER