

HALE

TRAILER

BRAKE & WHEEL

Resale Inventory

A023805

VIN: 156276



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	LOG TRAILER, DROP
DIMENSIONS	
LENGTH	46'-0" overall.
WIDTH	102".
HEIGHT	Nominal, 13'-6" high, top of frames approximately 61" high at front and 49" at rear.
DROP HEIGHT	12".
COUPLING	
COUPLER PLATE	5/16", plug welded reinforced structure.
KING PIN LOCATION	36" from front.
KING PIN	Bolted, 2" diameter, Jost KZ1008.
COUPLER HEIGHT	50"
STRUCTURE	Frame with "CAMBER".
FLANGES	3/8" x 6", 100 000 psi steel.
WEB	1/4" plate full length, 80 000 psi steel.
GOOSENECK	11" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, between main beams.
FLOOR	Checker plate 1/8" between main beams, full length, (no wood flooring at all).
FLOOR FASTENING	Fully welded on length, and at joints.
CORNERS	Square.
FENDERS	Checker plate 1/8", above truck wheels, sloping.
BRACING FOR LOADER	Stiffeners at 6" c/c on the outside of frames in the web, strap 4" x 1/2" at bottom in stiffener area.
ENDS	
FRONT RAIL	3/16" thick formed plate, 80 000 psi steel.
BUMPER	USA forestry type, with push & pull plates.
HEADBOARD	Boxes welded on front rail. To receive futur headboard, 96" high.
LOGGING	5 lengths of 8', 4 of 12', 3 of 16' or full lenght logs.
BUNKS	5 fixed sets of bunks with fabricated boxes. Located 60" and 72" c/c.
BUNKS	First 2 at front, 4 1/2" x 7" height, (flanges plate 1/4" 100 000 psi steel and webs one each side 3/16" 80 000 psi steel), double post boxes on first bunk.
BUNKS	Central section (7 bunks), 4 1/2" x 5" height, (flanges plate 1/4", 100 000 psi steel and webs one each side 3/16" 80 000 psi steel).
BUNKS	Rear, 11" x 9" height, (formed 3/16" "U" plate with 1/4" top plate, 80 000 psi steel), integrated into bumper with double boxes.
BOXE(S) DOUBLE BUNK ANGLES	Located on the 4TH bunk, (except on the first and last bunk). Steel ridge 1/2" x 1 1/2" installed on last bunk to hold tree length lumber.
STAKES	Qty: 20, ultra light, galvanised (G164), botton 4" x 4", 80 000 & 100 000 psi steel.



ITEM	DESCRIPTION
GLAD HANDS PROTECTOR RAISERS	3/8" thick plate, welded at front rail. One, aluminum extrusion 3" x 2" for a height same as the drop.
ELECTRICAL	
FRONT CONNECTOR FRONT ADD. CONNECTOR	7 ways (SAE J560), Phillips brand. 7 ways (ISO 3731), for auxiliary functions only. *** Air lift ***
ELECTRICAL SYSTEM MAIN SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, (tail lights with male pins #53252 (10 diodes), markers #47122 (2 1/2" dia.) #47493-3, licence light #60291-3).
TURN SIGNAL	Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber.
BACK UP LIGHT(S)	Sealed beam spot light (Grote #40-4411-00 in a closed back rubber grommet), Qty: 2
TAIL LIGHTS	Sealed beams (Grote DEL #53252, 10 diodes) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR	
SAND SHOES CRANK	Holland, Mark V (LGS-4F315). 10" x 11 1/2", solid axles. Road side.
BOGIE	
BASIC SUSPENSION SUSPENSION	Hendrickson INTRAAX AAT-30K, tridem, 60" spread. For axles with bearings HM 518445.
STROKE STOPPERS	Retaining chains for INTRAAX air suspensions with grounded axles.
MANUAL LIFT	Air lift Hendrickson "UBL" with air system Manac. Located: REAR AXLE
SPRINGS AXLE(S)	Air. LDA, 5 3/4" diameter, 25 000 lbs. capacity.
SPIDERS CAM SHAFTS	Welded. 10" long, 28 splines with enclosures.
TRACK DUST SHIELDS	77 1/2". Steel, clamped.
BRAKES BEARINGS	16 1/2" standard, H23 Hendrickson lining. HM 518445.
SLACK ADJUSTERS SEALS	Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS HUBS AND DRUMS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). KIC, 10 studs disc hubs, balanced drums 101.6 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminium wheels.
RIMS	Accuride, Accu-Lite, alum. EXTRA polished, 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts.
SPACERS	Wheel guard 10 holes. Located between the inside wheel and the drum and between two wheels.
TIRES	Continental, 11 R 24.5 HSR-2 16 ply (43.5")

