



Resale Inventory
A023942
VIN: 112153

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE



Product

Hauled: Milk

Barrel Description

Model	SRJ3 6500-1 T304, Stainless steel, Round, Jacketed, 3-A sanitary trailer
Code	3A Sanitary
Capacity	6500 gallons (shell full)
Compartments	One
Shape	Round
Shell Material	T304 Stainless steel, #4 finish, 12 gauge barrel. Two piece barrel with one circumferential weld.
Head Material	T304 Stainless steel, #4 finish, 12 gauge
Operating Pressure	Atmospheric
Design Temperature	212 Degrees F. (TEMPERATURE RATING OF 212 DEGREE F. WITH STANDARD COMBO/URETHANE INSULATION. TEMP RATING FOR OPTIONAL POLYSTYRENE IS 175 DEG F.)
Overall Length	42' 6"
Product	Various; to be compatible with the materials of construction.

Other Barrel Information

Heat	None
Plumbing	None
Intransit	None
Weld finish	W-5 inside

Construction

Rings	Stainless steel channel
Longerons	Stainless steel channel

Frame	Stainless steel, modified angle.
* Dam	Non-insulated stainless steel spill dam with stainless steel drains through ladder rail.
Dam Drains	None
Overturn Protection	None
Cleanout overturns	None
Manhole	Polar 19" stainless steel lid with dust cover, 4 hold-down. Stainless steel sanitary deck around manhole. Dust cover vent under hinge.
Gasket	Black gasket in cover..
Insulation	3/4" Polyurethane under 3" Polystyrene, R 18.5, 212 DEG F. max
Thermometer	None
Jacketing	22 gauge stainless steel bright finish
Jacket heads	18 gauge stainless steel #3 finish.
Underlayment	None
Static cable	No static cables installed.

Hose Carriers

Hose Carrier	None
Carrier Location	None

Lights and Wiring

Lights	12-volt, Truck-Lite grommet mount LED lamp system complying to FMVSS. Combination center marker / turn signals, one each side.
Wiring	Plug-in style harness system.
Rear Lights	Enclosed in stainless steel light boxes
Nose box	Standard 7 way, J560 receptacle with out circuit breakers.

Undercarriage

Upper 5th Wheel	5/16" Heavy duty with A.A.R. style double hubbed kingpin.
Paint	Fifth wheel plate painted black.
Landing Gear	SAF Holland Atlas 55, 2-speed, load bearing, sealed gear box, 55,000 lbs. rated lift capacity with 10"x10" swivel type sand shoes. Black Armour coating. No Lube, 5 year Warranty.
Frame	Stainless steel construction
Bracing	Stainless steel, with cross brace.
Crank location	Crank handle located on roadside

Tire carrier	None.
Suspension	Hendrickson Intraax AANT23K, tandem axle with standard 49" axle spacing. 5.75" diameter Hendrickson integrated axles.
Hangers	Stainless Steel hangers with soft coat applied to axle and trailing arm. (Weld-on suspension only)
* Dump valve	Manual Push / Pull dump valve with auto reset. System automatically refills when glad hands are reconnected. Sealco #110555S. Specify location. Note: Locate at roadside Landing gear area.
Subframe	3/16" stainless steel, with stainless steel fender supports.
Bumper	Non-code, stainless steel, bolt-on, (no under ride required, Wheels back exempt.)
Beam	Straight
Track	71-1/2" track
Spindle	OEM Standard P spindles (parallel) same inner and outer bearing
Wheel seals	OEM Standard
Hub & drums	Ready to Roll, Dura-light Hub with Cast Drum.
Brakes	OEM Standard
Anti-lock / Roll stability	OEM Standard 4S/2M with tandem axle roll stability for air-ride suspension.
Brake chambers	OEM Standard - Long stroke
Brake lining	OEM Standard Extended service, non-asbestos
Slack adjusters	OEM automatic slack adjuster.
Valves	OEM Standard
Gladhands	Gladhand, Phillips, Quick Release
Air system	One aluminum tank system. 2800 cu. in. each meeting FMVSS 121 D.O.T. specifications.
Emission Compliance	NA
Wheels	Alcoa Ultra One with clean buff finish, 22.5 x 8.25 aluminum.
Tires	11R-22.5 Cooper RM120, 14-ply. GHG2 CY 2020. CRR 5.8
Front	Aluminum, single contour, ribbed, front fender, each side.
Rear	Aluminum, double contour, ribbed, rear fender, each side.
Mud flaps	White, anti-sail and anti-spray with Polar logo, mounted front and rear.

Valving and Piping

* Seal provisions	0.25	Seal provisions on all openings
-------------------	------	---------------------------------

		Note: Two sets of seal tabs on Manhole, One near wingnut and the other set near hinge
Sump		3" stainless steel sanitary drain with mounting ring in rear head.
Discharge location		Rear of trailer.
Outlet valve		3" stainless steel 60TTF valve with aluminum dust cover, attached to mounting ring.
Venting and cleanouts		
Vacuum		Run-O-Vent in manhole cover
Cleanouts		None
Walkway and Ladder		
* Top center		24" x 26" aluminum, rear of manhole.
Ladder		Two Stainless steel tubular with grip steps and dual large platform step, bolt on
Ladder Location		One mounted curbside and roadside, near center of trailer.
Pump System		
Hydraulic Lines		None
Meter		None
Meter Installation		None
Cabinet		
Cabinet		None. No Cabinet installed.
Miscellaneous		
Decals		Standard warning and safety package. Decals in English.
Conspicuity Tape		Discontinuous tape
Customer Logo		None
Document holder		Truck Lite 97960 Certificate Holder. Install in standard location unless otherwise specified.
Calibration		Computer generated theoretical calibration chart, 1/4" increments. Based on innage.
Paint		None. No paint or primer installed on trailer.
Passivate		None
Warranty		Polar standard two year.
Tests		Standard testing.
Drawings		None.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.