

HALE

TRAILER

BRAKE & WHEEL



A024066
VIN: 044165

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Model: Axle Attachment
Capacity in tons: 60

1. DESIGN PARAMETERS

Type	Flip-up & removable
Framework	Fabricated
Suspension	30,000# Capacity Ridewell air
Axle attachment connections	Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections
Axle capacity	25,000# - GAWR 24,700#
Brakes	16-1/2" x 7" air actuated
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels DURA BRITE
Anti-lock brake system	None
Tires	Four (4) 275/70R22.5 (H) 16PR Cooper Roadmaster radial tires P.S.I. Tire inflation system from trailer
Bridge width	8'-6"
Axle frame height	41" frame; 37" bolster
Half bolster	Rear of axle 3 with 3/4" I.D. flag holders each side recessed into sides angled outward
Lash rings	2 at rear bent style
Lights and wiring	12 volt system with the following: All lights to be LED including mid-turn, excluding license plate light All marker/I.D. lights to be 3/4" bullet style 6 combination (3 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit (SN37025) Strobe lights with switch at rear Wire for battery back-up
Paint	Special color Blue Valspar no. (ref. KALT0357) urethane matched to a customer supplied paint chip (NON-METALLIC) with ZINC RICH primer and clear coat
Mudflaps	Talbert anti-sail
Additional design specifications	1) 2 rubber bumpers on top 2) 54" axle spacing 3) Over ride chains 4) Flexible/removable fenders over tires only. 5) Estimated empty weight: 3,000#
Compatibility	With SN44164

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.