

HALE

TRAILER

BRAKE & WHEEL



A024153
VIN: 000630

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Weight: 12,760

30ART 30 Ton Tridem Air Tilt/Air Ramp Tags

TRAILER

Overall Length 37 ft. 6 in.
Overall Width 102 in.
Weight lbs +/- 2% 12850, including options
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch 3 in. Pintle Eye, adjustable 5 position 17 in. to 31 in.

DECK

Deck Length 24 ft.
Main Frame Hi-Tensile Wide Flange 14 in. @ 30
Cross Members Hi-Tensile 6 in. Channel @ 8.2
Side Rail Hi-Tensile 8 in. Channel @ 11.5 Open on Inside
Air Tilt Deck * 4 Air Bags
Floor 1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear Dual 2 Speed
Step Bolt on, Located on Front Corner of Deck, Driver Side

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
Spread 49 in.
Suspension Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Air Tank(s) Aluminum
Bearings Oil Bath
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount c/w Cast Drums
Tires 235/75R17.5 16 ply
Wheels Alum. Wheel Pkg. 17.5 (12 polished)

BEAVERTAIL

Length 6 ft. @ 6 Degree Slope, Planked In

RAMPS

Length 38 in. x 76 in. Air Operated Planked

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Front Connector SAE J560 7 Pin
Lights LED CMVSS 108 / FMVSS 108
Lights Amber Flashing Strobe (Mounted in Ramps)
Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color Black

GENERAL SPECIFICATIONS

Mudflaps	2, 3 Pair Mudflaps with Brackets; 1 Set in Front of Lift Axles, 1 set in frot of 2nd axle and 1 Set at Rear
Toolbox	Full A Frame Mounted with Solid Bottom and Cover
Additional Toolbox	*NPO*: Aluminum Toolbox - 45 in. x 18 in. x 18 in., Driver Side
Additional Toolbox	*NPO*: Aluminum Toolbox - 45 in. x 18 in. x 18 in., Passenger Side
Load Securement	10 Pair of D-rings: 7 Pair on Main Deck, Evenly Spaced; 2 Pair on B/T (to be in line with main deck, approx 2 in. from top rail) customer aware of the ramp brace sitting on D ring); 1 Pair at Front of Deck on Main Beam at Headboard
Fenders	3/16 in. Deck Plate
Marker	Flag Holders (set of 4): customer wants them mounted straight not at an angle. Mount to outer corner of ramp

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.